

- Complies with American National Standard Z358.1-2009 when used exclusively as an eyewash
- 10-Gallon Pressurized Tank
- Twin Chrome-Plated Brass, Soft Flow, Eyewash Heads
- Highly Visible Yellow-Colored Hose Spray (S19-690 only)
- Universal Identification Sign and Inspection Tag Included
- Full, One-Year Warranty

Specifications

Ideal for providing emergency protection in areas where permanent water supply is not available. Supplements permanent eyewash fixture installations. Ten-gallon pressure tank is constructed of stainless steel. 35 $\frac{5}{8}$ " (905mm) high and 12 $\frac{1}{4}$ " (311mm) outside diameter. Weighs 23 lbs. empty and 86 lbs. full. Eyewash heads are chrome-plated brass. Tire filler valve with 0–160 PSI air gauge. 8' hand-held hose spray (S19-690 only) has chrome-plated metal parts. Flow from hose maintained approximately 3 $\frac{1}{2}$ minutes. Hose burst strength is 450 PSI. Hand-held hose sprayhead contains an antimicrobial agent to protect the sprayhead.

Standard Equipment

10-Gallon Tank

Stainless steel pressure tank has built-in carrying handles and resilient bottom. Tire filler valve with 0–160 PSI air gauge. Pressure relief valve prevents accidental over pressurization.

Eyewash

Twin chrome-plated brass, soft flow eyewash heads with automatic flow control stay-open valve. Protective dust covers are included. Hand operated by a large, highly visible stainless steel push handle. Flow from eyewash maintained approximately 15 minutes.

Hand-Held Hose Spray (S19-690 only)

8' (2438mm) yellow hose spray with hand-held squeeze-type valve, full-size spray nozzle, and hose clamp. All metal parts are chrome-plated. Flow maintained for approximately 3 minutes.

Concentrate (sold separately)

8 oz. bottle of water preservative mixes with 6–20 gallons of potable water. Preservative prevents bacteria, fungi, and algae growth in tank for up to four months. Concentrate is not included with tanks.



Personal eyewash equipment does not meet the criteria of plumbed or self-contained eyewash equipment. Personal eyewashes support plumbed or self-contained units but shall not replace them.

Model	Description
<input type="checkbox"/> S19-690	10-Gal. Portable, Pressurized Unit w/ Eyewash & Drench Hose
<input type="checkbox"/> S19-690LHS	10-Gal. Portable, Pressurized Unit w/ Eyewash only
<input type="checkbox"/> S19-865	Water preservative, 8 oz. concentrate, four bottles per carton

