







New Dryer Guide

		UNIQUE SELLING POINTS				
IMAGE	BRADLEY MODEL NUMBER	SPECIFICATIONS	CONVENIENCE	SAFETY	DESIGN	Applications
	2902-280000	Cover: Cast Iron, White	Adjustable Speed Motor	UL, CSA, CE certified	Only High Speed Surface Mounted ADA Compliant Dryer	Suitable for every type of restroom facility
		Voltage: Universal (100-120V, 208V, 220-240V)	Universal Voltage	Vandal Proof Operating System	Contemporary or High End	
		Surface Mounted, Sensor Operated	Surface Mounted - ADA compliant		Heavy Duty Construction	
		ADA Compliant	Retrofit to ADA:		New to the Market	
		Adjustable Speed Motor	*Bradley - 2869-28, 2870, 2873			
		*Dry Time: 10-15 seconds	*World Dryer - M/XM, A/XA, D/DA/DXA			
		*Noise Level: 64-74 dB rating				
		*Low power consumption: 1150W, 9.5A (110V) at max RPM level				
Vandal Proof Operating System: Automatic shutoff after 60 seconds of continuous use						
		UL, CSA, CE certified				
	2902-287300	Cover: Steel, White	Adjustable Speed Motor	UL, CSA, CE certified	Only High Speed Surface Mounted ADA Compliant Dryer	Suitable for every type of restroom facility
		Voltage: Universal (100-120V, 208V, 220-240V)	Universal Voltage	Vandal Proof Operating System	Contemporary or High End	
		Surface Mounted, Sensor Operated	Surface Mounted - ADA compliant		Heavy Duty Construction	
		ADA Compliant	Retrofit to ADA:		New to the Market	
		Adjustable Speed Motor	*Bradley - 2869-28, 2870, 2873			
		*Dry Time: 10-15 seconds	*World Dryer - M/XM, A/XA, D/DA/DXA			
		*Noise Level: 64-74 dB rating				
		*Low power consumption: 1150W, 9.5A (110V) at max RPM level				
Vandal Proof Operating System: Automatic shutoff after 60 seconds of continuous use						
		UL, CSA, CE certified				
	2902-287400	Cover: 304 Stainless Steel, Satin Finish	Adjustable Speed Motor	UL, CSA, CE certified	Only High Speed Surface Mounted ADA Compliant Dryer	Suitable for every type of restroom facility
		Voltage: Universal (100-120V, 208V, 220-240V)	Universal Voltage	Vandal Proof Operating System	Contemporary or High End	
		Surface Mounted, Sensor Operated	Surface Mounted - ADA compliant		Heavy Duty Construction	
		ADA Compliant	Retrofit to ADA:		New to the Market	
		Adjustable Speed Motor	*Bradley - 2869-28, 2870, 2873			
		*Dry Time: 10-15 seconds	*World Dryer - M/XM, A/XA, D/DA/DXA			
		*Noise Level: 64-74 dB rating				
		*Low power consumption: 1150W, 9.5A (110V) at max RPM level				
Vandal Proof Operating System: Automatic shutoff after 60 seconds of continuous use						
		UL, CSA, CE certified				
	2903-280000 2903-2800CE	Cover: Cast Iron, White	Equal to Bradley 2870-000000	UL and CSA	Traditional or Institutional	Suitable for many types of restroom facilities
		Voltage: 2903-280000 110-120V and 2903-2800CE 220-240V	Equal to Bradley 2870-490000	CE, VDE	Heavy Duty Construction	
		Surface Mounted, Sensor Operated				
		Fixed Nozzle				
		Noise Level: 70 dB rating				
		Low power consumption: 2903-280000 1850W, 16A and 2903-2800CE 2250W, 10A				
		Vandal Proof Operating System: Automatic shutoff after 60 seconds of continuous use				
		UL, CSA, CE, VDE certified				
	2904-280000 2904-2800CE	Cover: Cast Iron, White	Equal to Bradley 2873-000000	UL and CSA	Traditional or Institutional	Suitable for many types of restroom facilities
		Voltage: 2904-280000 110-120V and 2904-2800CE 220-240V	Equal to Bradley 2873-490000	CE, VDE	Heavy Duty Construction	
		Surface Mounted, Push Button Operated				
		Fixed Nozzle				
		Noise Level: 70 dB rating				
		Low power consumption: 2903-280000 1850W, 16A and 2903-2800CE 2250W, 10A				
		Vandal Proof Operating System: Automatic shutoff after 60 seconds of continuous use				
		UL, CSA, CE, VDE certified				
	2905-287300 2905-2873CE	Cover: Steel, White	Low Cost	UL and CSA	Contemporary	Suitable for Low-Medium Vandal restroom facilities
		Voltage: 2905-287300 110-120V and 2905-2873CE 220-240V		CE, VDE	Light to Medium Duty Construction	Suitable for Low-Medium Traffic restroom facilities
		Surface Mounted, Sensor Operated				
		Noise Level: 60 dB rating				
		Low power consumption: 2905-287300 1640W, 13.6A and 2905-2873CE 1640W, 7A				
		Induction Motor: Maintenance Free - no brushes				
		Vandal Proof Operating System: Automatic shutoff after 60 seconds of continuous use				
		UL, CSA, CE, VDE certified				