



# COL-2B, COL-3B, COL-4B, COL-5B, COL-6B Column Beach Showers, 2-6 Person

## Specifications

### Materials

All exposed parts are type 304 stainless steel or polished chrome-plated brass. Valve manifold is cast brass. Drain fitting is cast iron and supply inlets are copper tubing.

## Standard Equipment

### Flow Control

A 1.5 GPM (5.7 LPM) flow control is standard. Actual flow may vary, but will not exceed 2.0 GPM (7.6 LPM) max.

### Valve Type as Selected

For more information on each valve type, please visit the Shower Valves product section on [bradleycorp.com](http://bradleycorp.com).

### Column Shower

Constructed of type 304 stainless steel. Column and column cap are 16 gauge, and base flange is 13 gauge. Access panel located near bottom of column.

### Drain Type

Drain type A: supplies from below, vent off drain line.

### Supply Inlets

Constructed of 3/4" type "L" copper tubing.



The standard beach shower is arranged less drain slots.



Standard Selections (Must select one from each category)		
Model No. (select one)		
Description	Showerheads	Foot Sprays
<input type="checkbox"/> COL-2B 2-Person Column Shower*	1	1
<input type="checkbox"/> COL-3B 3-Person Column Shower*	2	1
<input type="checkbox"/> COL-4B 4-Person Column Shower	3	1
<input type="checkbox"/> COL-5B 5-Person Column Shower	4	1
<input type="checkbox"/> COL-6B 6-Person Column Shower	5	1
Drain Type (select one)		
<input type="checkbox"/> A Off-line vent with supplies from below		
Showerhead Height (select one)		
<input type="checkbox"/> 6'-0" Standard Height		
<input type="checkbox"/> 5'-6" Juvenile Height		
Valve Type (select one)		
<i>Single Tempered/Cold Supply</i>		
<input type="checkbox"/> AST Air Pushbutton		
<input type="checkbox"/> SV Single Compression Valve		

Showerhead Type (select one)	
<input type="checkbox"/> S15 Standard Showerhead (Flow Rate = 1.5 GPM/5.7 LPM)	
<input type="checkbox"/> S20 Standard Showerhead (Flow Rate = 2.0 GPM/7.6 LPM)	
Supply Stop Type (select one)	
<input type="checkbox"/> ST Stops in each Supply	
<input type="checkbox"/> NONE No Supply Stops	
Drain Variant Type (select one)	
<input type="checkbox"/> D Standard Drain	
<input type="checkbox"/> DG Dome Grate Drain	
<input type="checkbox"/> LD Less Column Drain	
Ship Drain in Advance (select one)	
<input type="checkbox"/> Y Yes **	
<input type="checkbox"/> N No, Ship Drain with Unit	
<input type="checkbox"/> NONE Less Column Drain Selected †	
Column Drain Slot Type (select one)	
<input type="checkbox"/> WS With Column Drain Slots	
<input type="checkbox"/> LS Less Column Drain Slots	
Clamping Ring Type (select one)**	
<input type="checkbox"/> CR Clamping Ring for Flashing	
<input type="checkbox"/> NONE No Clamping Ring for Flashing	
Ship Clamping Ring in Advance (select one)	
<input type="checkbox"/> Y Yes	
<input type="checkbox"/> N No, Ship Clamping Ring with Unit	
<input type="checkbox"/> NONE No Clamping Ring Selected	

\*Non-cancelable, non-returnable

\*\* Only available with D or DG Drain Variant Type

† Only available with LD Drain Variant Type

2.0 GPM and 2.5 GPM showerhead flow rates do not meet California Energy Commission 20 CCR T.20, Div. 2, 1601-1609