

- Model 2490 — Surface-Mounted with Sensor Activation *Bradex*[®]**
- Model 2493 — Surface-Mounted with Automatic Cut Mechanism**

Product Materials

UNIT: heavy gauge steel. Door fabricated of navy translucent high-impact plastic.

Capacity

Dispenses non-perforated roll towels up to 8" in diameter and 8" wide with core sizes from 1½"-2".

Operation

Model 2490: Towels are dispensed automatically when hands are placed at a natural position below the dispenser. Standard sheet length is nominal 12". Operates with 4 "D" size alkaline batteries. Batteries are not included. Automatic transfer system with 2¾" diameter stub roll capacity. Low battery indicator. Sheet is fully protected until dispensed.

Model 2490 only: Not recommended for high volume applications.

Model 2493: Towels are automatically and perfectly cut to an optimum hand dry towel length of 11½" (29cm). Dispenses most non-perforated roll towels up to 8" (20cm) wide when using 1½"-1¾" (38mm-41mm) I.D. cores. Low-pull force reduces tabbing.

Installation

Verify all rough-in dimensions prior to installation. Secure to wall using convenient mounting slots and use appropriate mounting devices supplied by installer.

Guide Specification

Dispenser sides and back shall be fabricated from heavy gauge steel, pre-treated and finished with a baked enamel. The cover shall be fabricated of navy translucent high-impact plastic.

MODEL 2490: Dispenser shall have a sensor activated dispensing mechanism. The sensor is to be located in place below the dispenser for natural hand position towel activation and retrieval. Dispenser shall be provided with a key activated spring lock, which can easily be converted to push-button operation. Dispenser shall include a transfer system which automatically start feeding the paper web of the top roll when the bottom roll is nearly depleted. The drive mechanism, transfer system and rollers and door shall be field replaceable. Complies with FCC regulation on EMC.

Overall dimensions: 10½"W x 15¾"H x 8¾"D.

MODEL 2493: Dispenser shall be provided with a key activated spring lock, which can easily be converted to a key knob.

Overall dimensions: 10½"W x 15¾"H x 8¾"D.

Washroom Accessories
Document No. 8214

Orders composed of products indicated as **Bradex**[®] will be available to ship in three days after receipt of order at the factory. There is no pricing penalty for this service from Bradley. This information is subject to change without notice.

Always consult local and national codes for proper installation guidelines. Conformity and compliance to local and national codes is the responsibility of the installer.

6-9-2009



Service Parts Available

Description	Part No.
<input type="checkbox"/> Key	P15-390
<input type="checkbox"/> Permanent Key Knob	P15-391
<input type="checkbox"/> Replacement Mechanism (Model 2490 only)	P15-392
<input type="checkbox"/> AC Conversion Pack (Model 2490 only)	P15-393
<input type="checkbox"/> SS Cover Option—Model Number 2490-PS200296	