

BRADLEY COMMERCIAL TOILET ACCESSORIES

This Bradley guide specification is useful in specifying toilet and bath accessories for institutional projects, including K-12 and university facilities, municipal facilities, and other projects demanding high durability, maintenance-friendly accessories. It includes an array of accessories to complete your project specification. This section is editable using common specification software editing tools, including selection of IP and SI units.

Bradley is a trusted leader in the commercial washroom equipment market, offering high quality accessories at a competitive price, fast delivery, and excellent customer service. Bradley offers a full line of washroom accessories for every application. From high-end office buildings to high-security prisons, Bradley has a product to meet any washroom accessory need.

Custom products are another Bradley specialty, from unusual configurations of grab bars, to modified sizes, Bradley will work with you to provide the products necessary to complete your project. Bradley Corporation serves a diverse customer base ranging from local business facilities to international corporations like Wal-Mart, General Motors, U.S. Postal Service, and AMC Theaters Corporation.

Architects, engineers, and specifiers look to Bradley Corporation for innovation in design and leadership in the development of environmentally conscious products. Bradley Corporation, a member of the U.S. Green Building Council, the Wisconsin Green Building Alliance, has several products earning certification by Greenguard Environmental Institute, and Greenguard Children and Schools program.

Bradley eases the specifying process with a seasoned customer service staff and a range of helpful information tools on an advanced website. Bradley's Universal Design Guide – Washrooms & Showers is available on the Bradley website as a helpful resource when planning commercial toilet room layout.

Bradley premium quality commercial products appear in the following CSI MasterFormat 2010™ Sections:

Section 10 21 13 – TOILET COMPARTMENTS (Mills® Metal, Plastic-laminate, Phenolic, and Plastic units)
Section 10 28 13.13 – COMMERCIAL TOILET ACCESSORIES (Institutional and commercial accessories)
Section 10 28 13.19 – HEALTHCARE TOILET ACCESSORIES (Patient care accessories)
Section 10 28 13.21 – WARM AIR DRYERS (Aerix® hand dryers)
Section 10 28 13.63 – DETENTION TOILET ACCESSORIES
Section 10 28 16 – BATH ACCESSORIES (Hospitality and commercial bath accessories)
Section 10 51 26 – PLASTIC LOCKERS (Lenox® Plastic Lockers)
Section 22 11 19 – DOMESTIC WATER PIPING SPECIALTIES (Thermostatic mixing valves)
Section 22 42 16.01 – COMMERCIAL LAVATORIES AND FAUCETS (Express® and Frequency® Single and multi-station lavatories)
Section 22 42 16.02 – COMMERCIAL LAVATORIES AND FAUCETS (Advocate® lavatories)
Section 22 42 16.03 – COMMERCIAL LAVATORIES AND FAUCETS (Verge™ lavatories)
Section 22 42 16.04 – COMMERCIAL LAVATORIES AND FAUCETS (Lav Decks™ lavatories)
Section 22 42 16.11 – COMMERCIAL SINKS AND FAUCETS
Section 22 42 23 – COMMERCIAL SHOWERS AND SHOWER VALVES
Section 22 42 33 – WASHFOUNTAINS (Sentry™, BradMate™, and Classic washfountains)
Section 22 43 00 – HEALTHCARE PLUMBING FIXTURES (Patient care lavatory units)
Section 22 45 00 – EMERGENCY PLUMBING FIXTURES (Halo™ Emergency eyewash fixtures and showers)
Section 22 46 00 – SECURITY PLUMBING FIXTURES
Contact Bradley Corporation, Menomonee Falls, WI 53051, Phone: 800-BRADLEY (800)272-3539, Fax: (262)251-5817, or visit the Bradley web site www.bradleycorp.com.

Bradley Corporation is an AIA/CES registered provider currently offering five programs earning one (1) HS&W Learning Unit each; several qualify for sustainable design (SD) credit. All active AIA members must successfully complete 18 learning unit (LU) hours each year.

GREENGUARD Certification ProgramSM is a service mark of GREENGUARD Environmental Institute. Mills[®], Aerix[®], Lenox[®], Express[®], Frequency[®], and Advocate[®] are registered trademarks of Bradley Corporation. Verge[™], Lav Decks[™], Sentry[™], BradMate[™], Diplomat[™], and Halo[™] are trademarks of Bradley Corporation.

**SECTION 10 28 13.13
COMMERCIAL TOILET ACCESSORIES**

PART 1 - GENERAL

1.1 SUMMARY

A. Section Includes

1. Public-use washroom accessories.
2. Public-use shower room accessories.
3. Childcare accessories.
4. Custodial accessories.

1.2 RELATED SECTIONS

Specifier: If retaining this optional article, delete any references below that do not apply to this project.

1. Division 08 Section "Mirrors" for monolithic glass mirrors.
2. Division 10 Section "Healthcare Toilet Accessories" for toilet accessories specific to healthcare facility patient care areas.
3. Division 10 Section "Warm Air Dryers" for hand dryers.
4. Division 10 Section "Detention Toilet Accessories" for toilet accessories specific to detention facility secure areas.

1.3 REFERENCES

Specifier: If retaining this optional article, edit to reflect standards cited in the completed section.

A. American National Standards Institute (ANSI):

1. ANSI A 117.1 - Accessible and Usable Buildings and Facilities.

B. ASTM International (ASTM):

1. ASTM A 653/A 653M - Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process.
2. ASTM A 666 - Standard Specification for Annealed or Cold-Worked Austenitic Stainless Steel Sheet, Strip, Plate, and Flat Bar.
3. ASTM A 1008/A 1008M- Standard Specification for Steel, Sheet, Cold-Rolled, Carbon, Structural, High-Strength Low-Alloy, High-Strength Low-Alloy with Improved Formability, Solution Hardened, and Bake Hardenable.
4. ASTM B 456 - Standard Specification for Electrodeposited Coatings of Copper Plus Nickel Plus Chromium and Nickel Plus Chromium.
5. ASTM C 1503 - Standard Specification for Silvered Flat Glass Mirror.
6. ASTM F 446 - Standard Consumer Safety Specification for Grab Bars and Accessories Installed in the Bathing Area.

C. US Federal Government:

1. U.S. Architectural & Transportation Barriers Compliance Board. Americans with Disability Act (ADA) and Architectural Barriers Act (ABA) Accessibility Guidelines for Buildings and Facilities.

1.4 ACTION SUBMITTALS

A. Product Data: For each product:

1. Manufacturer's product data sheets indicating operating characteristics, materials and finishes. Mark each sheet with product designation.
2. Mounting requirements and rough-in dimensions.

B. LEED Submittals:

1. Product data for Credit MR 4: Indicate percentages by weight of postconsumer and preconsumer recycled content, and product cost.

Specifier: Retain subparagraph below for LEED for Schools project. Below applies to accessories containing melamine components.

2. Laboratory Test Reports for Credit IEQ 4: For accessory components made from composite materials: Indicate compliance with testing and product requirements of the California Department of Health Services ""Standard Practice for the Testing of Volatile Organic Emissions from Various Sources Using Small-Scale Environmental Chambers.""

1.5 INFORMATION SUBMITTALS

- A. Sample warranty.
- B. Operation, care and cleaning instructions.

1.6 MAINTENANCE SUBMITTALS

- A. Furnish indicated spare parts that are packaged with identifying labels listing associated products.
- B. Operation and Maintenance data.

1.7 QUALITY ASSURANCE

- A. Source Limitations: For products listed together in the same Part 2 articles, obtain products from single source from single manufacturer.
- B. Manufacturer Qualifications: Approved manufacturer listed in this section, with minimum [5] years experience in the manufacture of product types. Manufacturers seeking approval must submit the following:
 1. Product data, including test data from qualified independent testing agency indicating compliance with requirements.
 2. Samples of each component of product specified.
 3. List of successful installations of similar products available for evaluation by Architect.

4. Submit substitution request not less than 15 days prior to bid date.

Specifier: Bradley product information includes detailed information regarding requirements of ADA, ICC A117.1, and Texas Accessibility Standards.

- C. Accessibility Requirements: Comply with requirements of ADA/ABA and with requirements of authorities having jurisdiction.

1.8 WARRANTY

- A. Special Mirror Warranty: Manufacturer's standard form in which manufacturer agrees to replace mirrors that develop visible silver spoilage or frame corrosion defects within specified warranty period.

1. Warranty Period: [15] years from date of Substantial Completion.

PART 2 - PRODUCTS

2.1 MANUFACTURERS

- A. Basis-of-Design Products: Subject to compliance with requirements, provide commercial toilet accessories manufactured by Bradley Corporation, Menomonee Falls, WI 53051, (800) 272-3539, fax: (262) 251-5817; Email info@BradleyCorp.com; Website: www.bradleycorp.com.

Specifier: Retain one of three paragraphs below based upon Project requirements.

1. Submit comparable products of one of the following for approval by Architect:
 - a. [Specifier: Insert name of manufacturer of comparable product.]
2. Submit requests for substitution in accordance with Instructions to Bidders and Division 01 General Requirements.
3. Provide specified product; Owner will not consider substitution requests.

2.2 MATERIALS

- A. Stainless Steel: ASTM A 666 Type 304 (18-8); satin finish exposed surfaces unless otherwise indicated.
- B. Steel Sheet: ASTM A 1008/A 1008M, Designation CS, manufacturer's standard thickness.
- C. Galvanized-Steel Sheet: ASTM A 653/A 653M, with G60 hot-dip zinc coating, manufacturer's standard thickness.
- D. Galvanized-Steel Mounting Devices: ASTM A 153/A 153M, hot-dip galvanized after fabrication.
- E. Fasteners:

1. Exposed: Screws, bolts, and other devices of same material as accessory unit and tamper-and-theft resistant.
 2. Concealed: Galvanized steel.
- F. Chrome Plating: ASTM B 456, Service Condition Number SC 2, moderate service.
- G. Mirrors: ASTM C 1503, Mirror Glazing Quality, clear-glass mirrors, nominal 6.0 mm thick.
- H. ABS Plastic: Acrylonitrile-butadiene-styrene resin formulation.

2.3 PUBLIC-USE WASHROOM ACCESSORIES

Bradley Surface Mounted Toilet Tissue Dispensers:

505	Single roll, controlled delivery, surface mount, exposed roll, chrome plated die cast zinc.
522	Same as 505, but dual roll version.
5053	Single roll, controlled delivery, surface mount, exposed roll, epoxy coated bent aluminum.
5054	Single roll, controlled delivery, surface mount, exposed roll, chrome plated steel.
5224	Same as 5054, but dual roll version.
5061	Single roll, controlled delivery, surface mount, exposed roll, bright polished stainless steel.
5071	Single roll, controlled delivery, surface mount, exposed roll, die cast aluminum.
5241	Same as 5071, but dual roll version.
508	Single roll, non-controlled delivery, surface mount, exposed roll, chrome plated cast brass.
508-32	Single roll, non-controlled delivery, surface mount, exposed roll, chrome plated die cast Zamac alloy.
523	Same as 508-32, but dual roll version.
5084	Single roll, non-controlled delivery, surface mount, exposed roll, satin finish stainless steel.
5234	Same as 5084, but dual roll version
5085	Single roll, non-controlled delivery, surface mount, exposed roll, bright polished stainless steel.
5235	Same as 5085, but dual roll version
5106	Single roll, non-controlled delivery, surface mount, hinged hood over roll, bright polished stainless steel.
5126	Same as 5106, but dual roll version
515	Sheet tissue, surface mount, vandal resistant hinged locking cover, satin finish stainless steel.
5262	Single roll, non-controlled delivery, surface mount, satin finish stainless steel, with stainless steel shelf.
5263	Same as 5262, but dual roll version.
5402	Single roll, non-controlled delivery, surface mount, vandal resistant hinged locking cover, spare roll, satin finish stainless steel.
5A10	Double roll, non-controlled delivery, surface mount, exposed roll, satin finish stainless steel. Designed with unique dual curved geometry.

A. Toilet Tissue Roll Dispenser, Surface Mount **TTDS**:

1. Basis of Design: **Bradley Corp., Model [____]**.

2. Application: [At each water closet, unless otherwise indicated.] [Where indicated] [insert location description].

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Capacity: [Single roll] [Double roll] [plus spare] [Sheet tissue] dispenser.
4. Finish and Base Material: [Chrome-plated die cast zinc] [Die-cast Zamac alloy] [Epoxy-coated bent aluminum] [Cast aluminum] [Chrome-plated steel] [Bright-polished stainless steel] [Satin-finish stainless steel] with polymer spindles.
5. Roll Access: [Exposed.] [Enclosed.] [Under hinged cover.]
6. Delivery: [Controlled.] [Non-controlled.] [Non-controlled at accessible water closets.]
7. Mounting: [Surface-mounted.] [Surface-mounted under shelf.]
8. [Service Access: Vandal resistant lock.]

Bradley Recessed Mounted Toilet Tissue Dispensers:

- 510 Single roll, non-controlled delivery, recessed mount, exposed roll, chrome plated cast brass.
- 5102 Single roll, non-controlled delivery, recessed mount, exposed roll, bright finish stainless steel.
- 5103 Single roll, non-controlled delivery, recessed mount, hinged hood over roll, bright polished stainless steel.
- 5123 Same as 5103, but dual roll version.
- 5104 Single roll, non-controlled delivery, recessed mount, exposed roll, satin finish stainless steel.
- 5105 Single roll, non-controlled delivery, recessed mount, exposed roll, spare roll, polished stainless steel.
- 5A00 Dual roll, non-controlled delivery, recessed mount, exposed roll, satin finish stainless steel.
- 5124 Dual roll, non-controlled delivery, recessed mount, exposed roll, satin finish stainless steel.
- 5125 Dual roll, non-controlled delivery, recessed mount, exposed roll, bright polished stainless steel.
- 5127 Dual roll, non-controlled delivery, recessed mount, hinged hood over roll, bright polished stainless steel.

B. Toilet Tissue Roll Dispenser, Recessed Mount TTDR:

1. Basis of Design: **Bradley Corp., Model [____]**.
2. Application: [At each water closet, unless otherwise indicated.] [Where indicated] [insert location description].

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Capacity: [Single roll] [Double roll] [plus spare] dispenser.
4. Finish and Base Material: [Chrome-plated cast brass] [Bright-polished stainless steel] [Satin-finish stainless steel] with polymer spindles.
5. Roll Access: [Exposed.] [Under hinged cover.]
6. Delivery: Non-controlled.
7. Mounting: Recessed mounted.

Bradley Recessed Mounted Enclosed Roll Toilet Tissue Dispensers:

- 5412 Single roll, non-controlled delivery, recessed mount, enclosed roll, spare roll, vandal resistant hinged locking cover, satin finish stainless steel.

C. Toilet Tissue Enclosed Roll Dispenser, Recessed Mount **TTDR**:

1. Basis of Design: **Bradley Corp., Model 5412.**
2. Application: [At each water closet, unless otherwise indicated.] [Where indicated] [insert location description].

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Capacity: Single roll plus spare roll.
4. Material: Satin finish stainless steel, with polymer spindles.
5. Roll Access: Enclosed.
6. Delivery: Non-controlled.
7. Mounting: Recessed.
8. Service Access: Vandal resistant lock.

Bradley Shared Partition-Mounted Toilet Tissue Dispensers:

- | | |
|------|---|
| 5A20 | Partition mounted, serves two compartments: Single roll plus spare roll for each compartment, non-controlled delivery, recess mount, enclosed roll, satin finish stainless steel. Vandal resistant hinged locking cover in each compartment. Designed with unique dual curved geometry. |
| 5422 | Partition mounted, serves two compartments: Single roll plus spare roll for each compartment, non-controlled delivery, recessed mount, enclosed roll, satin finish stainless steel. Vandal resistant hinged locking cover in each compartment. |

D. Shared, Partition Mounted Toilet Tissue Dispensers **TTDP**:

1. Basis of Design: **Bradley Corp., Model 5422.**
2. Application: [At each paired water closet, unless otherwise indicated.] [Where indicated] [insert location description].

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Capacity: Single roll plus spare roll.
4. Material: Stainless steel with polymer spindles.
5. Finish: Satin finish stainless steel.
6. Roll Access: Enclosed.
7. Delivery: Non-controlled.
8. Mounting: Thru-partition.
9. Service Access: Vandal resistant lock.

Bradley Jumbo Roll Toilet Tissue Dispensers:

- | | |
|------|--|
| 5424 | Single roll, up to 10 inch diameter, surface mounted, satin finish stainless steel. Vandal resistant hinged locking cover. |
| 5425 | Dual roll, 9 inch diameter, surface mounted, satin finish stainless steel. Vandal resistant hinged locking cover. |

E. Toilet Tissue Jumbo Roll Dispenser, Surface Mount **TTJ**:

1. Basis of Design: **Bradley Corp., Model [____].**

2. Application: [At each water closet, unless otherwise indicated.] [Where indicated] [insert location description].

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Mounting: Surface mounted, accepts up to 10 inch (254 mm) roll.
4. Core Adapters: As required to accommodate tissue roll with 1-1/2 inch (38 mm), 2-1/8 inch (54 mm), and 3 inch (76 mm) core.

Bradley Combination Toilet Tissue Dispensers:

- | | |
|---------|--|
| 5912 | Recessed mounted, dual roll, non-controlled delivery, exposed roll, seat cover dispenser, and 1.0 gallon plastic waste receptacle with stainless steel push flap door, satin finish stainless steel. Vandal resistant hinged locking covers. This unit can coordinate with grab bars. |
| 5912-10 | Semi-recessed mounted, dual roll, non-controlled delivery, exposed roll, seat cover dispenser, and 1.0 gallon plastic waste receptacle with stainless steel push flap door, satin finish stainless steel. Vandal resistant hinged locking cover. Projects 1-1/4 inch, cannot coordinate with grab bars. |
| 5912-11 | Surface mounted, dual roll, non-controlled delivery, exposed roll, seat cover dispenser, and 1.0 gallon plastic waste receptacle with stainless steel push flap door, satin finish stainless steel. Vandal resistant hinged locking covers. This unit cannot coordinate with grab bars. |
| 5912-69 | Surface mounted, dual roll, non-controlled delivery, exposed roll, seat cover dispenser, and 1.0 gallon plastic waste receptacle with stainless steel push flap door, reverse-hinged door, satin finish stainless steel. Vandal resistant hinged locking cover. Reverse hand door. This unit projects 1-1/4 inch, and with single door, it cannot coordinate with grab bars. |
| 5922 | Recess mounted, dual roll, non-controlled delivery, exposed roll, seat cover dispenser, satin finish, stainless steel. Vandal resistant hinged locking cover in one compartment. This unit can coordinate with grab bars on one side. |
| 5922-10 | Semi Recess mounted, dual roll, non-controlled delivery, seat cover dispenser, satin finish, stainless steel. Vandal resistant hinged locking cover in one compartment. This unit cannot coordinate with grab bars. |
| 5922-11 | Surface mounted, dual roll, non-controlled delivery, exposed roll, seat cover dispenser, satin finish, stainless steel. Vandal resistant hinged locking cover in one compartment. This unit cannot coordinate with grab bars. |
| 5922-69 | Recess mounted, dual roll, non-controlled delivery, exposed roll, seat cover dispenser, satin finish, stainless steel. Vandal resistant hinged locking cover in one compartment. Reverse hand door. This unit projects 1-1/4 inch, and with single door, it cannot coordinate with grab bars. |
| 5932 | Recess mounted, with seat cover dispenser and 1.7 gallon plastic waste receptacle with stainless steel push flap door, recessed mount on one side, satin finish stainless steel. Vandal resistant hinged locking cover in one compartment. This unit can coordinate with grab bars on one side. |
| 5932-10 | Semi-Recess mounted, with seat cover dispenser and 1.7 gallon plastic waste receptacle with stainless steel push flap door, satin finish stainless steel. Vandal resistant hinged locking cover in one compartment. This unit cannot coordinate with grab bars. |
| 5932-11 | Surface mounted, with seat cover dispenser and 1.7 gallon plastic waste receptacle with stainless steel push flap door, satin finish, stainless steel. Vandal resistant hinged locking cover in one compartment. This unit cannot coordinate with grab bars. |
| 5942 | Recess mounted, with dual roll, exposed roll, non-controlled delivery, and 1.0 gallon plastic waste receptacle with stainless steel push flap door for one compartment, satin finish stainless |

	steel. Vandal resistant hinged locking cover in one compartment. This unit can coordinate with grab bars on one side.
5942-10	Semi-Recess mounted, dual roll, exposed roll, non-controlled delivery, and 1.0 gallon plastic waste receptacle with stainless steel push flap door for one compartment, satin finish stainless steel. Vandal resistant hinged locking cover in one compartment. This unit cannot coordinate with grab bars.
5942-11	Surface mounted, dual roll, exposed roll, non-controlled delivery, and 1.0 gallon plastic waste receptacle with stainless steel push flap door for one compartment, satin finish stainless steel. Vandal resistant hinged locking cover in one compartment. This unit cannot coordinate with grab bars.

A. Combination Toilet Tissue Dispensers **CTTD**: Units with toilet tissue dispenser, seat cover dispenser[, and waste receptacle].

1. Basis of Design: **Bradley Corp., Model [____]**.
2. Application: **[At each water closet, unless otherwise indicated.] [Where indicated] [insert location description]**.

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Finish and Base Material: Satin finish stainless steel, with polymer spindles.
4. Waste Receptacle: Plastic, 1.7 gallon (6.5 liters), with stainless steel push flap door.
5. Seat Cover Dispenser.
6. Capacity: Dual roll.
7. Roll Access: Exposed.
8. Delivery: Non-controlled.
9. Mounting: **[Flush, one side] [Recessed, one side.] [Semi-recessed, one side] [Surface, one side.]**
10. Service Access: Vandal resistant lock, single door.
11. Grab Bar Coordination: **[Not required] [Required]**.

Bradley Shared Partition Mounted Combination Toilet Tissue Dispensers:

591	Partition mounted, serves two compartments. Dual roll for each compartment, non-controlled delivery, exposed roll, with seat cover dispenser and 0.88 gallon plastic waste receptacle with stainless steel push flap door, vandal resistant hinged locking cover in each compartment, recessed mount; satin finish stainless steel.
5911	Partition mounted, serves two compartments. Dual roll for each compartment, non-controlled delivery, exposed tissue rolls on left, with seat cover dispenser, and 0.88 gallon plastic waste receptacle with stainless steel push flap door, vandal resistant hinged locking cover in each compartment, flush installation on one side, recessed mount; satin finish stainless steel.
5911-69	Partition mounted, serves two compartments. Dual roll for each compartment, non-controlled delivery, exposed tissue rolls on right, seat cover dispenser, and 0.88 gallon plastic waste receptacle with stainless steel push flap door, flush installation on one side, recessed mount. Vandal resistant hinged locking cover in one compartment with flush mount on opposite side to coordinate with grab bar; satin finish stainless steel.
5941	Partition mounted, serves two compartments. Dual roll for each compartment, non-controlled delivery, exposed roll, and 0.88 gallon plastic waste receptacle with stainless steel push flap door for each compartment, flush mount on one side, satin finish stainless steel. Vandal resistant hinged locking cover in one compartment. Coordinates with grab bars on one side.

592	Partition mounted, serves two compartments. Dual roll for each compartment, non-controlled delivery, exposed roll, seat cover dispenser for each compartment, recessed mount, satin finish stainless steel. Vandal resistant hinged locking cover in one compartment.
5921	Partition mounted, serves two compartments. Dual roll for each compartment, non-controlled delivery, exposed tissue rolls on left, seat cover dispenser for each compartment, flush mount on one side, satin finish stainless steel. Vandal resistant hinged locking cover in one compartment. Coordinates with grab bars on one side.
5921-69	Partition mounted, serves two compartments. Dual roll for each compartment, non-controlled delivery, exposed tissue rolls on right, seat cover dispenser for each compartment, flush mount on one side, satin finish, satin finish stainless steel. Vandal resistant hinged locking cover in one compartment. Coordinates with grab bars on one side.
594	Partition mounted, serves two compartments. Dual roll, non-controlled delivery, exposed roll, and 1.0 gallon plastic waste receptacle with stainless steel push flap door for each compartment, flush mount on one side, satin finish stainless steel. Vandal resistant hinged locking cover in one compartment. This unit can coordinate with grab bars on one side.

- B. Shared Partition Mounted Combination Toilet Tissue Dispensers **CTTD**: Dual-compartment units with toilet tissue dispenser, seat cover dispenser[, and waste receptacle].
1. Basis of Design: **Bradley Corp., Model [____]**.
 2. Application: [At each paired water closet, unless otherwise indicated.] [Where indicated] [insert location description].

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Finish and Base Material: Satin finish stainless steel, with polymer spindles.
4. Waste Receptacle: Plastic, [0.88 gallon (3.3 liters)] [1 gallon (3.8 liters)] [1.7 gallon (6.5 liters)], with stainless steel push flap door.
5. Seat Cover Dispenser.
6. Capacity: Dual roll for [one] [each] compartment.
7. Roll Access: Exposed.
8. Delivery: Non-controlled.
9. Mounting: [Flush, one side] [Recessed, one side.] [Semi-recessed, one side] [Surface, one side.]
10. Service Access: Vandal resistant lock, [single] [double] door.
11. Grab Bar Coordination: [Not required] [One-side] [Two-sides].

- C. Toilet Tissue (Folded) Dispenser **TTF**:

1. Basis of Design: **Bradley Corp., Model 515**.
2. Application: [At each water closet, unless otherwise indicated.] [Where indicated] [insert location description].

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Finish and Base Material: Satin finish stainless steel.
4. Capacity: 700 double-fold or 1,250 single-fold tissue sheets, minimum.
5. Mounting: Surface mounted.
6. Service Access: Vandal resistant lock on hinged door.

Bradley Combination (Folded) Paper Towel Dispenser and Waste Containers. Units are arranged in decreasing size of waste receptacles:

- 2A05 Combination assembly including towel dispenser for 800 multi-fold and 600 C-fold paper towels, and 12 gallon satin finish stainless steel waste receptacle, vandal resistant lock. -00 recessed mount; -10 semi-recessed; -11 surface mount. Designed with unique dual curved geometry.
- 2037 Combination assembly including towel dispenser for 1,100 single fold, 800 multi-fold, or 600 C-fold towels, and 11.2 gallon removable plastic waste receptacle, satin finish stainless steel, vandal resistant lock. -00 recessed mount; -10 semi-recessed mount; -11 surface mount.
- 225 Combination assembly including towel dispenser for 1,000 single fold, 800 multi-fold, or 600 C-fold towels, and 9.2 gallon removable plastic waste receptacle, satin finish stainless steel, vandal resistant lock. -00 recessed mount; -10 semi-recessed mount; -11 surface mount.
- 2251 Combination assembly including towel dispenser for 450 multi-fold, or 250 C-fold towels, and 5.3 gallon removable plastic waste receptacle, satin finish stainless steel. Vandal resistant hinged locking cover over towel dispenser and waste compartment. -00 recessed mount; -10 semi-recessed mount; -11 surface mount.
- 2017 Combination assembly including towel dispenser for 1,100 single fold, 800 multi-fold, or 600 C-fold towels, and 4.9 gallon removable plastic waste receptacle, satin finish stainless steel. Vandal resistant hinged locking cover over towel dispenser and waste compartment. -00 recessed mount; -10 semi-recessed mount; -11 surface mount.
- 2252 Combination assembly including towel dispenser for 1,000 single fold, 700 multi-fold, or 400 C-fold towels, and 4.9 gallon removable plastic waste receptacle, satin finish stainless steel. Vandal resistant hinged locking cover over towel dispenser and waste compartment. -00 recessed mount; -10 semi-recessed mount; -11 surface mount.
- 2027 Combination assembly including towel dispenser for 800 multi-fold, or 600 C-fold towels, and 3.3 gallon removable plastic waste receptacle, satin finish stainless steel. Vandal resistant hinged locking cover over towel dispenser and waste compartment. -00 recessed mount; -10 semi-recessed mount; -11 surface mount.
- 2291 Combination assembly including towel dispenser for 475 multi-fold, or 350 C-fold towels, and 2 gallon removable stainless steel waste receptacle, satin finish stainless steel. Vandal resistant hinged locking cover over towel dispenser. -00 recessed mount; -10 semi-recessed mount; -11 surface mount.
- 2297 Combination assembly including towel dispenser for 475 multi-fold, or 350 C-fold towels, and 1.7 gallon removable plastic waste receptacle, satin finish stainless steel. Vandal resistant hinged locking cover over towel dispenser and waste receptacle. -00 recessed mount; -10 semi-recessed mount; -11 surface mount.
- 229 Combination assembly including towel dispenser for 200 multi-fold, or 100 C-fold towels, and 1.25 gallon removable stainless steel waste receptacle, satin finish stainless steel. Vandal resistant hinged locking cover over towel dispenser and waste compartment. -00 recessed mount; -10 semi-recessed mount; -11 surface mount.
- 2A95 Combination assembly designed for field installation of customer-provided towel dispenser. Removable 21 gallon stainless steel waste receptacle. -10 semi-recessed; -11 surface mount.

D. Combination Paper Towel (Folded) Dispenser/Waste Receptacle **PTFW:**

1. Basis of Design: **Bradley Corp., Model [____]**.
2. Application: **[Where indicated] [insert location description]**.

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Materials: Stainless steel, rolled at exposed edges.
4. Finish and Base Material: Satin stainless steel.
5. Mounting: [Recessed] [Semi-recessed] [Surface].
6. Towel Capacity by Types:
 - a. [1,100] [1,000] [710] [400] single fold towels.
 - b. [800] [700] [525] [500] [475] [450] multi-fold towels.
 - c. [600] [500] [400] [370] [350] [300] [200] [100] C-fold towels.
7. Towel Delivery Method: Bottom pull.
8. Waste Receptacle:
 - a. Plastic, [1.7 gallons (6.4 liters)] [3.3 gallons (12.5 liters)] [4.9 gallons (18.5 liters)] [5.3 gallons (20 liters)] [9.2 gallons (35 liters)] [11.2 gallons (42 liters)].
 - b. Stainless steel, [1.25 gallons (4.7 liters)] [2 gallons (7.6 liters)].
9. Service Access: Vandal resistant lock, same key for each compartment door.
10. Options: [Mirrored door] [Cup dispenser] [Self-closing flap door] [Waste container liner].

Bradley Paper Towel (Folded) Dispensers:

2A00	Towel dispenser for 800 multi-fold or 600 C-fold towels, satin finish stainless steel. Vandal resistant hinged locking. -00 recessed mount; -10 semi-recessed mount.
2A09	Towel dispenser designed for field installation of customer-provided towel dispenser, satin finish stainless steel. Vandal resistant hinged locking. -00 recessed mount; -10 semi-recessed; -11 surface-mounted.
2A10	Towel dispenser for 800 multi-fold or 600 c-fold towels, satin finish stainless steel. Vandal resistant hinged locking. -11 surface mounted.
247	Towel dispenser for 1,000 single fold, 800 multi-fold, or 500 C-fold towels, satin finish stainless steel. Vandal resistant hinged locking. -00 recessed mount; -10 semi-recessed mount; -11 surface mount.
250-15	Surface mounted towel dispenser for 525 multi-fold, or 400 C-fold towels. Satin finish stainless steel. Vandal resistant hinged locking cover.
250-33	Surface mounted towel dispenser for 525 multi-fold, or 400 C-fold towels. Steel cabinet with white enamel finish. Vandal resistant hinged locking cover.
251-15	Surface mounted towel dispenser for 400 single fold towels. Satin finish stainless steel. Vandal resistant hinged locking cover.
252	Surface mounted towel dispenser for 350 multi- fold or 200 C-fold towels. Satin finish stainless steel. Vandal resistant hinged locking cover.

E. Paper Towel (Folded) Dispensers PTFD:

1. Basis of Design: **Bradley Corp., Model [____]**.
2. Application: [Where indicated] [insert location description].

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Finish and Base Material: Satin stainless steel, rolled at exposed edges.
4. Mounting: [Recessed] [Semi-recessed] [Surface].
5. Towel Capacity by Types:

- a. [1,100] [1,000] [710] [400] single fold towels.
 - b. [800] [700] [525] [475] [450] multi-fold towels.
 - c. [600] [500] [400] [370] [350] [300] [200] [100] C-fold towels.
6. Towel Delivery Method: Bottom pull.
 7. Service Access: Vandal resistant lock.

Bradley 3-in-1 Paper Towel (Folded) Dispenser and Waste Containers.

- 270 Towel dispenser for 710 single fold, 500 multi-fold, or 370 C-fold towels, satin finish stainless. Vandal resistant hinged locking door. Dispenser lever requires less than 5 pounds force to operate. -00 recessed mount; -10 semi-recessed mount; -11 surface mount.
- 279-49 Identical to 270, but CE certified and suitable for export to Europe.

F. Paper Towel (3-in-1 Folded) Dispensers PTFD:

1. Basis of Design: **Bradley Corp., Model [____]**.
2. Application: [Where indicated] [insert location description].

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Finish and Base Material: [Satin stainless steel, rolled at exposed edges.] [Plastic laminate on melamine, color as selected from manufacturer's full line.]
4. Mounting: [Recessed] [Semi-recessed] [Surface].
5. Towel Capacity: 710 single fold, 500 multi-fold, or 370 C-fold towels.
6. Towel Delivery Method: Bottom pull.
7. Service Access: Vandal resistant lock.

Bradley Recessed Behind-Mirror Mounted Multi-Purpose Paper Towel (Folded) Dispensers :

- 198 Recessed mounted assembly for mounting in 1/2 inch wall board surfaces behind mirror, including towel dispenser for 800 multi-fold or 600 C-fold towels, satin finish stainless steel. Vandal resistant hinged locking cover over towel dispenser. For 5/8 inch gypsum board, use 1985.
- 1981 Recessed mounted assembly for mounting behind mirror, including towel dispenser for 800 multi-fold or 600 C-fold towels, satin finish stainless steel. Vandal resistant hinged locking cover over towel dispenser.

G. Recessed Behind-Mirror Multi-Purpose Paper Towel (Folded) Dispensers MPTFD:

1. Basis of Design: **Bradley Corp., Model [____]**.
2. Application: [At each lavatory, unless otherwise indicated.] [Where indicated] [insert location description].

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Finish and Base Material: Satin finish stainless steel.
4. Single-fold towel minimum capacity: [800] multi-fold or [600] C-fold.
5. Soap Capacity: [40 ounces (1180 ml)] [100 ounces (2950 ml)].
6. Mounting: [Recessed mounted] [Recessed behind-mirror mounted].
7. Service Access: Vandal resistant lock, same key for each compartment door.

Bradley Multi-Purpose Towel Dispenser/Soap Dispensers:

- 1471 Recessed mounted assembly including towel dispenser for 250 multi-fold or 150 C-fold towels, and soap dispenser with reservoir and pump. Soap valve has chrome plated brass housing and ABS plastic mechanism. Vandal resistant hinged locking cover over towel dispenser and soap dispenser. -00 recessed mount; -11 surface mount.

H. Multipurpose Paper Towel (Folded) Dispenser/Soap Dispensers **PTSD:**

1. Basis of Design: **Bradley Corp., Model [____]**.
2. Application: [Where indicated] [insert location description].

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Materials: Stainless steel, rolled at exposed edges.
4. Finish: Satin stainless steel.
5. Mounting: [Recessed] [Semi-recessed] [Surface].
6. Towel Capacity: 800 multi-fold or C-fold towels.
7. Soap Capacity: [40 ounces (1180 ml)] [100 ounces (2950 ml)].
8. Towel Delivery Method: Bottom pull.
9. Service Access: Vandal resistant lock, same key for each compartment door.

Bradley Center-Pull Roll Paper Towel Dispensers:

- 2479 Recessed mounted center-pull towel dispenser for up to 9 inch wide, 9 inch diameter roll towel stock, satin finish stainless steel with ABS dispensing component. Vandal resistant hinged locking towel door. -00 recessed mount; -11 semi-recessed mount.

I. Paper Towel (Center Pull Roll) Dispenser **PTRD:**

1. Basis of Design: **Bradley Corp., Model [____]**.
2. Application: [Where indicated] [insert location description].

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Finish and Base Materials: Satin stainless steel, rolled at exposed edges.
4. Mounting: [Recessed] [Semi-recessed] [Surface].
5. Towel Capacity: Center pull towel roll, maximum 9 by 9 inches (229 by 229 mm).
6. Towel Delivery Method: Center pull.
7. Service Access: Vandal resistant lock.

Bradley Combination Roll Paper Towel Dispenser and Waste Containers:

- 2A15 Lever operated roll towel dispenser for one standard 8 inch wide core, delivers preset length of towel 5 ½ inches, 21 gallon satin finish stainless steel waste receptacle. Vandal resistant hinged door over waste receptacle. -10 semi-recessed; -11 surface mount.
- 2A25 Sensor activated roll towel dispenser for one standard 8 inch wide core, delivers preset length of towel 10" per operation, 21 gallon satin finish stainless steel waste receptacle. Vandal resistant hinged door over waste receptacle. -10 semi-recessed; -11 surface mount.
- 227 Recessed mounted assembly including lever operated towel dispenser for 8 or 9 inch wide, 800 feet long roll paper towel, and 18 gallon removable plastic waste receptacle, satin finish stainless steel. Dispenser lever requires less than 5 pounds force to operate. Vandal resistant

	hinged locking cover over towel dispenser and waste compartment. -00 recessed mount; -10 semi-recessed mount; -11 surface mount.
2271	Recessed mounted assembly including cabinet for towel dispenser, and 18 gallon plastic waste receptacle, satin finish stainless steel. Vandal resistant hinged locking cover over towel dispenser and waste compartment. Towel dispenser is not included with unit; Bradley Model 2494 is recommended. -00 recessed mount; -10 semi-recessed mount; -11 surface mount.
2277	Recessed mounted assembly including lever operated towel dispenser for 8 or 9 inch wide, 800 feet long roll paper towel, and 10.5 gallon removable plastic waste receptacle, satin finish stainless steel. Dispenser lever requires less than 5 pounds force to operate. Vandal resistant hinged locking cover over towel dispenser and waste compartment. -00 recessed mount; -10 semi-recessed mount; -11 surface mount.

J. Combination Paper Towel (Roll) Dispenser/Waste Receptacle **PTRWR**:

1. Basis of Design: **Bradley Corp., Model [____]**.
2. Application: **[Where indicated] [insert location description]**.

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Finish and Base Material: **[Satin stainless steel, rolled at exposed edges.] [Plastic laminate on melamine, color as selected from manufacturer's full line.]**
4. Mounting: **[Recessed] [Semi-recessed] [Surface]**.
5. Towel Capacity by Types: **[8 or 9 inch by 800 ft (203 or 229 mm by 244 m).] [Towel unit provided separately.]**
6. Towel Delivery Method: **[ADA-compliant] Lever operated.**
7. Waste Receptacle: Plastic, **[10.5 gallons (40 liters)] [18 gallons (68 liters)]**.
8. Service Access: Vandal resistant lock.
9. **[Waste container liner]**.

Bradley Paper Towel Roll Dispenser:

2482-11	Surface mounted push bar operated towel dispenser for 8 inch wide, 800 foot roll paper towel, satin finish stainless. Vandal resistant hinged locking door. Dispenser bar requires less than 5 pounds force to operate. Operating mechanism is enameled steel.
2A01	Lever operated towel dispenser for 8 inch wide standard roll paper towel stock, satin finish stainless. Vandal resistant hinged locking door. Dispenser lever requires less than 5 pounds force to operate. -00 recessed; -10 semi-recessed; -11 surface mount.
2483	Surface mounted lever operated towel dispenser for 8 or 9 inch wide, 800 foot roll paper towel stock, satin finish stainless. Vandal resistant hinged locking door. Dispenser lever requires less than 5 pounds force to operate.
2484	Lever operated towel dispenser for 8 or 9 inch wide, 800 foot roll paper towel stock, satin finish stainless. Vandal resistant hinged locking door. Dispenser lever requires less than 5 pounds force to operate. -00 recessed; -10 semi-recessed mount.
2A02	Sensor activated towel dispenser for 8 inch wide standard roll paper towel stock, satin finish stainless. Vandal resistant hinged locking door. Dispenser lever requires less than 5 pounds force to operate. -00 recessed; -10 semi recessed; -11 surface mount.
2494	Surface mounted, sensor-activated towel dispenser for 8 or 9 inch wide, 800 foot long roll paper towel stock. High impact plastic construction. Power Source: Four "D"cell alkaline batteries.
2495	Surface mounted, lever operated towel dispenser for 8 or 9 inch wide, 800 foot long roll paper towel stock. High impact plastic construction.

K. Paper Towel (Roll) Dispenser **PTRD**:

1. Basis of Design: **Bradley Corp., Model [____]**.
2. Application: [Where indicated] [insert location description].

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Finish and Base Material: [Satin stainless steel, rolled at exposed edges.] [High impact plastic.]
4. Mounting: [Recessed] [Semi-recessed] [Surface].
5. Towel Capacity: 8 or 9 inch by 800 ft (203 or 229 mm by 244 m).
6. Towel Delivery Method: [Lever operated] [Push bar operated] [Sensor activated, battery powered].
7. Service Access: Vandal resistant lock.

Bradley Deck-Mounted Liquid Soap Dispensers:

- 6315 Deck mounted, sensor operated liquid soap dispenser. 5-1/2 inch spout. Power: 4 "D" cell batteries. Include LED indicators for low battery and low soap level. Fabricated from chrome plated plastic. 27 or 54 oz. soap bottle. -KT: Includes batteries and 1000 shot soap.
- 6322 Deck mounted, hand pump operated liquid soap dispenser. 2-1/2 inch spout. Pump only. Plunger and spout fabricated from stainless steel. -67: 16 oz. stainless steel soap bottle. -68: 32 oz. plastic soap bottle.
- 6324 Deck mounted, hand pump operated liquid soap dispenser. 4 inch spout. Pump only. Plunger and spout fabricated from stainless steel. -67: 16 oz. stainless steel soap bottle. -68: 32 oz. plastic soap bottle.
- 6326 Deck mounted, hand pump operated liquid soap dispenser. 6 inch spout. Pump only. Plunger and spout fabricated from stainless steel. -67: 16 oz. stainless steel soap bottle. -68: 32 oz. plastic soap bottle.
- 6334 Deck mounted, hand pump operated liquid soap dispenser, including plastic 16 oz. soap bottle. Plunger and spout fabricated from chrome plated brass.

L. Liquid-Soap Dispenser **SD**:

1. Basis of Design: **Bradley Corp., Model [____]**.
2. Application: [Where indicated] [insert location description].

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Description: Designed for dispensing soap in liquid form from under-counter reservoir.
4. Materials: [Chromed plastic.] [Stainless steel plunger and spout, brass escutcheon.] [Plastic] [Stainless steel] globe.
5. Operation: [Sensor operated.] [Manual pump.]
6. Mounting: Vertically oriented, surface mounted.
7. Spout: [2-1/2 inch (63 mm)] [4 inch (102 mm)] [5-1/2 inch (140 mm)] [6 inch (152 mm)].
8. Soap Capacity: [16 ounces (475 ml)] [24 ounces (710 ml)] [27 ounces (800 ml).] [32 ounces (945 ml)] [40 ounces (1180 ml)] [44 ounces (1300 ml)] [54 ounces (1,600 ml).] [80 ounces (2360 ml)].

Bradley Recessed Wall-Mounted Liquid Soap Dispensers:

- 643 Recessed mounted, satin finish stainless steel with high impact polystyrene lined soap vessel. Chrome plated brass soap valve with ABS plastic mechanism. 32 oz. capacity. Vandal resistant hinged locking cover.
- 6437 Recessed mounted, satin finish stainless steel with high impact polystyrene lined soap vessel. Face plate and soap vessel are an integral assembly. Chrome plated brass soap valve with ABS plastic mechanism. 32 oz. capacity. Vandal resistant hinged locking cover.
- 644 Recessed mounted, satin finish stainless steel. Face plate and soap vessel are an integral assembly. Chrome plated brass soap valve with ABS plastic mechanism. 40 oz. capacity. Vandal resistant hinged locking cover.

Bradley Surface Wall-Mounted Liquid Soap Dispensers:

- 6A00 Surface mounted automatic, liquid soap dispenser with 27 oz. capacity, satin finish stainless steel. Can also dispense hand sanitizer and foam soap. Red light indicates low battery.
- 648 Surface mounted assembly including top mounted 16 oz. translucent plastic container, zinc plated steel mounting bracket with 360 degree swivel for easy globe removal. Push-up valve made of chrome plated moving parts, stainless steel spring, and neoprene washers.
- 6481 Same as Model 648, but with chrome plated plastic, non-swivel mounting bracket.
- 650 Surface mounted assembly including top mounted 32 oz. translucent plastic container, chrome plated ABS plastic mounting bracket. Push-up valve made of ABS plastic moving parts, and stainless steel spring.
- 6501 Surface mounted assembly including top mounted 24 oz. translucent plastic container, chrome plated ABS plastic mounting bracket. Push-up valve made of ABS plastic moving parts, and stainless steel spring.
- 6531 Surface mounted, satin finish stainless steel housing and soap vessel. Includes metal wall plate mechanically locked to dispenser. Chrome plated brass soap valve with ABS plastic mechanism. 44 oz. capacity. Removable cover for service.
- 6542 Surface mounted, satin finish stainless steel housing and soap vessel. Includes metal wall plate mechanically locked to dispenser. Chrome plated brass soap valve with ABS plastic mechanism. 40 oz. capacity. Keyed fill hole for service.
- 655 Surface mounted, satin finish stainless steel housing and soap vessel. Includes metal wall plate mechanically locked to dispenser. Push up type chrome plated brass soap valve with ABS plastic mechanism. 40 oz. capacity. Keyed fill hole for service.
- 6562 Surface mounted, satin finish stainless steel housing and soap vessel. Includes metal wall plate mechanically locked to dispenser. Chrome plated brass soap valve with ABS plastic mechanism. 40 oz. capacity. Keyed fill hole for service.
- 657 Surface mounted, high polish chrome plated brass container and plastic soap container. Includes stainless steel wall plate. Push in type chrome plated plastic valve with ABS plastic mechanism. 12 oz. capacity. Keyed fill hole for service, with locking chain.
- 658-30 Surface mounted, satin finish stainless steel round housing and powdered soap vessel. Includes chrome plated steel wall plate. Push type knob to dispense soap powder. 32 oz. capacity. Keyed tilting lid for service.
- 6583 Surface mounted, satin finish stainless steel rectangular housing and powdered soap vessel. Includes chrome plated steel wall plate. Push type knob to dispense soap powder through adjustable mechanism. 32 oz. capacity. Keyed fill hole for service.
- 661 Surface mounted, shelf type, satin finish stainless steel housing and soap vessel. Includes metal wall plate. Single chrome plated brass soap valve with ABS plastic mechanism. 80 oz. capacity. Hinged cover with latches for service.
- 662 Same as Model 661, but with 2 soap valves.

6843	Surface mounted dispenser with stainless steel spout projecting 9 inches from face of wall. Foot pump operated. ABS plastic dispenser with translucent polyethylene plastic soap container, molded rubber foot pump, and vinyl tubing.
6563	Surface mounted, satin finish stainless steel rectangular housing and liquid soap vessel. Includes chrome plated steel wall plate. Black ABS plastic push valve to dispense liquid soap through adjustable mechanism. 40 oz. capacity. Keyed fill hole for service.

M. Liquid-Soap Dispenser **SD**:

1. Basis of Design: **Bradley Corp., Model [____]**.
2. Application: [Where indicated] [insert location description].

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Housing: [Satin stainless steel.] [Chrome-plated brass.] [Chromed plastic.] [Translucent plastic.]
4. Operation: [Sensor operated.] [Stainless steel manual pump.] [Chrome-plated brass and ABS plastic manual pump.] [ABS plastic manual pump.] [Foot pump operated with 9 inch (229 mm) stainless steel spout.]
5. Mounting: [Surface mounted.] [Recessed mounted.]
6. Soap Capacity: [16 ounces (475 ml)] [24 ounces (710 ml)] [27 ounces (800 ml).] [32 ounces (945 ml)] [40 ounces (1180 ml)] [44 ounces (1300 ml)] [54 ounces (1,600 ml).] [80 ounces (2360 ml)].

Bradley Wall-Mounted Enclosed Waste Receptacles:

315-35	Recessed enclosed waste receptacle, satin stainless steel with seamless welded construction. 22 ga. flange, cabinet, and push flap door. 18 ga. door with piano hinge and tumbler lock. Removable 9.2 gal. leakproof molded plastic waste receptacle insert. -10: Semi-recessed 3-1/2 inches, projecting 4 inches. -11: Surface-mounted, projecting 7-1/2 inches.
3157	Contemporary Series recessed enclosed waste receptacle, satin stainless steel with seamless welded construction. 22 ga. flange, cabinet, and push flap door. 18 ga. door with 1/2 inch return, concealed piano hinge and two tumbler locks. Removable 9.2 gal. leakproof molded plastic waste receptacle insert. -10: Semi-recessed 3 inches, projecting 3-3/4 inches. -11: Surface-mounted, projecting 6-3/4 inches.
3251	Recessed enclosed waste receptacle, satin stainless steel with seamless welded construction. 22 ga. flange, cabinet, and push flap door embossed "PUSH". 18 ga. door with piano hinge and tumbler lock. Removable 2.8 gal. leakproof molded plastic waste receptacle insert. -10: Semi-recessed 2 inches, projecting 2 inches. -11: Surface-mounted, projecting 4 inches.
3257	Contemporary Series recessed enclosed waste receptacle, satin stainless steel with seamless welded construction. 22 ga. flange, cabinet, and push flap door. 18 ga. door with 1/2 inch return, concealed piano hinge and tumbler lock. Removable 2.8 gal. leakproof molded plastic waste receptacle insert. -10: Semi-recessed 1-1/2 inches, projecting 2-1/2 inches. -11: Surface-mounted, projecting 4 inches.

N. Waste Receptacle, Wall-Mounted, Enclosed **WR**:

1. Basis of Design: **Bradley Corp., Model [____]**.
2. Application:

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Mounting: [Recessed] [Semi-recessed] [Surface-mounted].
4. Capacity: [9.2 gal. (34.8 L)] [2.8 gal. (10.6 L)].
5. Material and Finish: Stainless steel, No. 4 finish (satin).
6. Cabinet and Flange: 22 ga.

Specifier: Select one of two door subparagraphs below. Second paragraph describes "Contemporary Series" unit. Third paragraph describes Bradley "Accent Series" unit.

7. Door: 18 ga., with piano hinge, tumbler lock, and push flap door[, embossed "PUSH"].
8. Door: 18 ga. overlay style, with concealed piano hinge, tumbler lock, and push flap door.
9. Removable Insert: Molded plastic.

Bradley Wall-Mounted Waste Receptacles:

- | | |
|------|--|
| 3A05 | Recessed waste receptacle, satin stainless steel with seamless welded construction. 22 ga. Flange and cabinet. Removable 12 gal. 20 ga. Stainless steel waste receptacle secured to cabinet with tumbler lock. -00: recessed 3-13/16 inches, projecting 4-7/8 inches. -10: semi-recessed 2", projecting 6-11-16 inches. -11: surface-mounted projects 8-11/16 inches. |
| 334 | Recessed waste receptacle, satin stainless steel with seamless welded construction. 22 ga. flange and cabinet. Removable 18 gal. 22 ga. stainless steel waste receptacle secured to cabinet with tumbler lock. Optional hinged satin stainless steel receptacle cover with optional push flap door. Optional vinyl –coated nylon receptacle liner. Projects 8-3/4 inches. -10: Semi-recessed 2 inches, projecting 10-3/4 inches. -11: Surface-mounted, projecting 12-3/4 inches. |
| 344 | Recessed waste receptacle, satin stainless steel with seamless welded construction. 22 ga. flange and cabinet. Removable 12 gal. 22 ga. stainless steel waste receptacle secured to cabinet with tumbler lock. Optional hinged satin stainless steel receptacle cover with optional push flap door embossed "PUSH". Optional vinyl –coated nylon receptacle liner. Projects 4-3/4 inches. -10: Semi-recessed 2 inches, projecting 6-3/4 inches. -11: Surface-mounted, projecting 8-3/4 inches. |
| 346 | Recessed waste receptacle, satin stainless steel with seamless welded construction. 22 ga. flange and cabinet. Removable 12 gal. 22 ga. stainless steel waste receptacle secured to cabinet with tumbler lock. Optional hinged satin stainless steel receptacle cover with optional push flap door embossed "PUSH". Optional vinyl –coated nylon receptacle liner. Projects 2-3/4 inches. -10: Semi-recessed 4 inches, projecting 4-3/4 inches. -11: Surface-mounted, projecting 8-3/4 inches. |
| 3A15 | Surface-mounted waste receptacle, satin stainless steel with seamless welded construction. Fixed 16.5 gallon, 20 ga. Stainless steel waste receptacle secured to wall through rear mounting holes. |
| 355 | Surface-mounted waste receptacle, satin stainless steel with seamless welded construction. Fixed 20.6 gal. 22 ga. stainless steel waste receptacle secured to wall through rear mounting holes. Optional hinged satin stainless steel receptacle cover with optional push flap door embossed "PUSH". Optional vinyl –coated nylon receptacle liner installed with hook and loop fasteners. Projects 12-1/2 inches. |
| 356 | Surface-mounted waste receptacle, satin stainless steel with seamless welded construction. Fixed 16.5 gal. 22 ga. stainless steel waste receptacle secured to wall through rear mounting holes. Optional hinged satin stainless steel receptacle cover. Optional vinyl –coated nylon receptacle liner installed with hook and loop fasteners. Projects 12-1/2 inches. |
| 357 | Surface-mounted waste receptacle, satin stainless steel with seamless welded construction. Fixed 6.5 gal. 22 ga. stainless steel waste receptacle secured to wall through rear mounting |

holes. Optional hinged satin stainless steel receptacle cover. Optional vinyl –coated nylon receptacle liner installed with hook and loop fasteners. Projects 6-1/2 inches.

359 Surface-mounted facial tissue receptacle, satin stainless steel with seamless welded construction. Fixed 1.5 gal. 22 ga. stainless steel waste receptacle secured to wall through rear mounting holes. Optional replaceable wet-strength paper liners. Projects 4-1/2 inches.

A. Waste Receptacle, Wall-Mounted **WR**:

1. Basis of Design: **Bradley Corp., Model [____]**.

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

2. Mounting: **[Recessed]** **[Semi-recessed]** **[Surface-mounted]**.
3. Capacity: **[20.6 gal. (78 L)]** **[18 gal. (68 L)]** **[16.5 gal. (62.5 L)]** **[12 gal. (45.4 L)]** **[6.5 gal. (24.6 L)]**.
4. Material and Finish: Stainless steel, 22 ga., No. 4 finish (satin).
5. Receptacle: 22 ga., seamless, secured to cabinet with tumbler lock.

Other Bradley Waste Receptacles and Accessories:

377 Free-standing waste receptacle, satin stainless steel with seamless welded construction, equipped with vinyl wall bumper strip and rubber feet. 13 gal. 22 ga. capacity. Optional hinged satin stainless steel swing top. -36: 21 gal. -38: 36-gal.

P10-696 Waste chute for under-counter waste receptacles. Stainless steel, drawn one-piece construction, 6 inch diameter opening, self-rimming.

B. Waste Receptacle, Freestanding **WR**:

1. Basis of Design: **Bradley Corp., Model [____]**.

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

2. Location: **[Under waste chute]** **[As indicated]**.
3. Capacity: **[13 gal. (49.2 L)]** **[21 gal. (79.5 L)]** **[36 gal. (136.3 L)]**.
4. Material and Finish: Stainless steel, 22 ga., No. 4 finish (satin).
5. Receptacle: 22 ga., seamless, with vinyl wall bumper strip and rubber feet.

Specifier: Retain optional swing top or waste chute as required for project.

6. Swing top: Stainless steel, with 2-side access.
7. Countertop Waste Chute: Stainless steel, self-rimming, 6 inch (152 mm) diameter.

Bradley Fixed Grab Bars:

812 1-1/2 inch o.d. 18 ga stainless steel tubing. 3-1/8 inch diameter 13 ga flanges; 22 ga stainless steel escutcheons. Satin Safety grip, high polish, or safety grip with high polish finishes. 817: Less escutcheons.

832 1-1/4 inch o.d. 18 ga stainless steel tubing. 3-1/8 inch diameter 13 ga flanges; 22 ga stainless steel escutcheons. Satin safety grip, high polish, or safety grip with high polish finishes. 837: less escutcheons.

852 1-inch o.d. 18 ga stainless steel tubing. 3-1/8 inch diameter 13 ga flanges; 22 ga stainless steel escutcheons. Satin safety grip, high polish, or safety grip with high polish finishes. 857: less escutcheons.

A. Fixed Grab Bars [GB36], [GB42], [GB48]:

1. Basis of Design, Fixed Grab Bar: **Bradley Corp., [Model 812 series 1-1/2 inch (38 mm) diameter] [Model 832 series 1-1/4 inch (32 mm) diameter] [Model 852 series 1 inch (25 mm) diameter]**.
2. Application: [Where indicated] [insert location description].
3. Mounting: [Flanges with concealed fasteners] [Exposed flanges].
4. Material: Stainless steel, 0.05 inch (1.27 mm) thick.
5. Length: [As designated] [As indicated].
6. Finish: [Satin] [Safety grip] [High polish] [Safety grip with high polish].

Bradley Swinging Grab Bars:

- 8170-158 1-1/2 inch o.d. 18 ga stainless steel tubing. 3/16 inch thick wall and floor flanges; 22 ga satin finish on exposed surfaces. Includes alignment notches and pins to hold bar when swung into support and departure positions. -1: Includes integral toilet tissue dispenser.
- 8370-101 1-1/4 inch o.d. 18 ga stainless steel tubing with satin finish on exposed surfaces. Satin or safety grip finishes. 14 ga stainless steel wall plate. Lowers to horizontal position for support, and raises to vertical position for departure. Projects 29 inches.
- 8370-102 1-1/4 inch o.d. 18 ga stainless steel tubing with satin finish on exposed surfaces. Satin or safety grip finishes. 14 ga stainless steel wall plate. Lowers to horizontal position for support, and raises to vertical position for departure. Projects 34 inches.
- 8370-103 1-1/4 inch o.d. 18 ga stainless steel tubing with satin finish on exposed surfaces. Satin or safety grip finishes. 14 ga stainless steel wall plate. Lowers to horizontal position for support, and raises to vertical position for departure. Includes integral toilet tissue dispenser with ABS plastic spindle.

B. Swinging Grab Bars **GBS**:

1. Basis of Design, Horizontal Swing Away Grab Bar: **Bradley Corp., Model 8170 series, 1-1/2 inch (38 mm) diameter by 29-3/4 inch (756 mm) length.**
2. Basis of Design, Vertical Swing Up Grab Bar: **Bradley Corp., Model 8370 series, 1-1/4 inch (32 mm) diameter by [29 inch (737 mm) length] [34 inch (864 mm) length, with integral toilet tissue dispenser]**.
3. Application: [Where indicated] [insert location description].
4. Mounting: [Flanges with concealed fasteners] [Exposed flanges].
5. Material: Stainless steel, 0.05 inch (1.27 mm) thick.
6. Finish: [Satin] [Safety grip] [High polish] [Safety grip with high polish].

Bradley Sanitary Product Vendors:

- 4A20 Stainless steel cabinet with satin finish. One vending mechanism each for sanitary napkins and tampons. Vending mechanisms owner set from free, \$0.10, \$0.25, \$0.50, \$1.00. Vend capacity: 18 sanitary napkins and 28 tampons. Hinged door includes vandal resistant locks. Adjustable flange permits recessed or semi-recessed mounting, or may be discarded for surface mounting. Coin box lock is different than cabinet key. -00 recessed mount; -11 surface mount.

401	Stainless steel cabinet with satin finish. One vending mechanism each for sanitary napkins and tampons. Vending mechanisms owner set from free, \$0.10, \$0.25, \$0.50, or \$1.00. Vend capacity: 30 sanitary napkins and 28 tampons. Hinged door includes two vandal resistant locks. Coin box lock is different than cabinet key. Adjustable flange permits recessed or semi-recessed mounting, or may be discarded for surface mounting.
4017	Stainless steel cabinet with satin finish. One vending mechanism each for sanitary napkins and tampons. Vending mechanisms can be selected from free, \$0.10, \$0.25, \$0.50, or \$1.00. Vend capacity: 30 sanitary napkins and 28 tampons. Hinged door includes two vandal resistant locks. Coin box lock is different than cabinet key. -00 recessed mount; -10 semi-recessed mount; -11 surface mount
407	Stainless steel cabinet with satin finish. One vending mechanism each for sanitary napkins and tampons. Vending mechanisms can be selected from free, \$0.10, \$0.25, \$0.50, or \$1.00. Vend capacity: 18 sanitary napkins and 28 tampons. Hinged door includes two vandal resistant locks. Coin box lock is different than cabinet key. -00 recessed mount; -11 surface mount

C. Sanitary Product Vendor **SPV**:

1. Basis of Design: **Bradley Corp.**, [____].
2. Application: [Where indicated] [insert location description].

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Mounting: [Recessed] [Semi-recessed] [Surface].
4. Operation: Coin operated [Free] [\$0.10] [\$0.25] [\$0.50] \$1.00].
5. Finish and Base Material: Stainless steel, satin finish.

Sanitary Product Disposal Units:

4A00	Recessed and semi-recessed mount. Stainless steel construction with satin finish. 1.5 gallon Napkin disposal with push flap door. Removable plastic disposable. – 00 recessed; -10 semi-recessed mount.
4721-15	Partition mounted, serves two compartments. Stainless steel construction, with satin finish. 1.5 gallon waste container. Push flap door on each side. Vandal resistant lock on one side.
4A11	Partition mounted, serves two compartments. Stainless steel construction with satin finish. 1.5 gal. surface-mounted napkin disposal with self-closing push flap door. Removable plastic disposal.
4722-1015	Semi-recessed. Stainless steel construction, with satin finish. 1.5 gallon waste container. Push flap door. Vandal resistant lock.
4722-15	Surface mounted. Stainless steel construction, with satin finish. 1.5 gallon waste container. Push flap door. Vandal resistant lock.
4731-15	Recessed. Stainless steel construction, with satin finish. 1.5 gallon waste container. Push flap door. Vandal resistant.
4737	Recessed mounted. Stainless steel construction, with satin finish. 1.5 gallon waste container. Push flap door. Vandal resistant lock. -00 recessed mount; -10 semi-recessed mount; -11 surface mount.
4A10	Surface mounted. Stainless steel construction, with satin finish. 1.5 gal. surface mounted napkin disposal with hinged cover. Accepts all after-market industry liners.

- 4781-15 Surface mounted. Stainless steel construction, with satin finish. 1.25 gallon waste container with wax paper liner. Lift flap door. Vandal resistant lock for service.
- 4791-15 Same as 4781-15, but includes 28 square inch shelf.

D. Sanitary Product Disposal Unit **SDU**:

1. Basis of Design: **Bradley Corp., [____]**.
2. Application: **[Where indicated] [insert location description]**.

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Mounting: **[Recessed] [Semi-recessed] [Surface] mounted**.
4. Receptacle: Removable, with vandal-proof lock, capacity **[1.25 gal (4.7 L)] [1.5 gal (5.7 L)]**.
5. Finish: Stainless steel satin.

Bradley Seat Cover Dispensers:

- 582 Partition mounted, serves two compartments. Capacity: 1,000 single fold or half fold seat covers. Satin finish stainless steel. Vandal resistant hinged locking cover in each compartment.
- 5A40 Surface mounted. Capacity: 250 single fold covers. Satin finish stainless steel. Vandal resistant bottom hinged locking cover for easy filling. Unit has spring clip dispensing mechanism.
- 583 Surface mounted. Capacity: 500 single fold or half fold seat covers. Satin finish stainless steel. Vandal resistant hinged locking cover.
- 5831 Surface mounted. Capacity: 250 single fold or half fold seat covers. Satin finish stainless steel. Insert seat covers through opening in bottom of unit.
- 584 Recessed. Capacity: 500 single fold or half fold seat covers. Satin finish stainless steel. Vandal resistant hinged locking cover.
- 5847 Recessed. Capacity: 500 single fold or half fold seat covers. Satin finish stainless steel. Vandal resistant hinged locking cover.

E. Seat-Cover Dispenser **SCD**:

1. Basis of Design: **Bradley Corp., [____]**.
2. Application: **[Where indicated] [insert location description]**.

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Mounting: **[Recessed] [Semi-recessed] [Surface] mounted**.
4. Capacity: **[500] [250] single fold or half-fold covers**.
5. Finish: Stainless steel satin.
6. Service: **[Vandal proof lock access.] [Latch.]**

Bradley Purse Shelves:

- 7510 Surface mounted stainless steel shelf. Stainless steel support brackets welded to shelf. Satin finish. Standard lengths: 12 to 112 inches by 10 inches deep.
- 7512 Same as Model 7510, but 12 inches deep.

755	Surface mounted stainless steel shelf. Stainless steel integral end support brackets and intermediate brackets welded to shelf. Satin finish. Standard lengths: 6 to 112 inches by 5 inches deep. 756: 6 inches deep. 758: 8 inches deep.
760	Recessed stainless steel shelf. Satin finish. Dimensions: 18 by 8-1/2 by 4 inches deep.
790	Surface mounted die cast zinc fold down shelf. Chrome plated finish. Held in upright position by spring. Returns to upright position when weight is removed. Maximum load: 150 pounds.

F. Purse Shelf **PS**:

1. Basis of Design: **Bradley Corp., Model [____]**.
2. Application: **[Where indicated] [insert location description]**.

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Mounting: Surface mounted on wall or partition **[, fold-down]**.
4. Material: **[Stainless steel.] [Die cast zinc.]**
5. Finish: **[Stainless steel satin] [Chrome plated.]**

Bradley Mirrors:

740	Fixed tilt, stainless steel frame with welded stiffeners. Galvanized steel back secured to frame with concealed fasteners. Mirror: 1/4 inch float glass, triple silver plated with electro copper plated layer and thermosetting, infrared cured paint backing with Poly-Glaze finish. Conforms to ASTM C 1036. Includes wedge of extruded polystyrene between mirror and steel back. Options: Tempered glass; laminated glass; polished No. 8 stainless steel; bright annealed stainless steel; Plexiglass. Sizes 18 by 30, 18 by 36, and 24 by 36 inches are standard; other sizes are available. Maximum size: 48 (W) by 48 (H) inches. For tempered glass, one dimension must be greater than 25 inches.
7405	Fixed tilt, stainless steel frame with welded stiffeners and 5-1/2 inch deep shelf the full width of the mirror unit. Galvanized steel back secured to frame with concealed fasteners. Mirror: 1/4 inch float glass, triple silver plated with electro copper plated layer and thermosetting, infrared cured paint backing with Poly-Glaze finish. Conforms to ASTM C 1036. Includes wedge of extruded polystyrene between mirror and steel back. Options: Tempered glass; laminated glass; polished No. 8 stainless steel; bright annealed stainless steel; Plexiglass. Sizes 18 by 30, 18 by 36, and 24 by 36 inches are standard; other sizes are available. Maximum size: 48 (W) by 48 (H) inches. For tempered glass, one dimension must be greater than 25 inches.
747	Surface mount, frameless with clip fasteners. Mirror: 1/4 inch float glass, triple silver plated with electro copper plated layer and thermosetting, infrared cured paint backing with Poly-Glaze finish. Conforms to ASTM C 1036. Options: Tempered glass mirror. 24 by 36 inches is standard; other sizes are available. Maximum size: 60 (W) by 96 (H) inches. For tempered glass, one dimension must be greater than 25 inches.
748	Surface mount 304 stainless steel mirror with No. 8 bright finish. Tempered Masonite bonded to mirror with adhesive. Maximum size: 47-1/2(W) by 72 (H) inches.
7481	Surface mount bright annealed, stretcher leveled, 430 stainless steel mirror. Tempered Masonite bonded to mirror with adhesive. Maximum size: 47-1/2(W) by 72 (H) inches.

780	<p>Stainless steel angle frame with stiffeners, and bevel at mirror surface to assure full contact. Galvanized steel back secured to frame with concealed fasteners. Mirror: 1/4 inch float glass, triple silver plated with electro copper plated layer and thermosetting, infrared cured paint backing with Poly-Glaze finish. All edges protected by shock-absorbing neoprene tubing. Conforms to ASTM C 1036. Includes wedge of extruded polystyrene between mirror and steel back. Includes cold rolled steel wall hangers.</p> <p>Options: Tempered glass; laminated glass; polished No. 8 stainless steel; bright annealed stainless steel; Plexiglass. Sizes 18 by 30, 18 by 36, 24 by 36, and 24 by 60 inches are standard; other sizes are available. Maximum size: 120 (W) by 72 (H) inches. For tempered glass, one dimension must be greater than 25 inches.</p>
7805	<p>Same as Model 780, but with 5-1/2 inch stainless steel shelf. Maximum size: 96 (W) by 60 (H) inches. For tempered glass, one dimension must be greater than 25 inches.</p>
781	<p>Stainless steel channel frame with stiffeners. Galvanized steel back secured to frame with concealed fasteners. Mirror: 1/4 inch float glass, triple silver plated with electro copper plated layer and thermosetting, infrared cured paint backing with Poly-Glaze finish. All edges protected by shock-absorbing neoprene tubing. Conforms to ASTM C 1036. Includes wedge of extruded polystyrene between mirror and steel back. Includes cold rolled steel wall hangers.</p> <p>Options: Tempered glass; laminated glass; polished No. 8 stainless steel; bright annealed stainless steel; Plexiglass. Sizes 18 by 24, 18 by 30, 18 by 36, 24 by 30, 24 by 36, 24 by 36 tempered glass, and 24 by 60 inches are standard; other sizes are available. Maximum size: 120 (W) by 72 (H) inches. For tempered glass, one dimension must be greater than 25 inches.</p>
7815	<p>Same as Model 781, but with 5-1/2 inch stainless steel shelf. Size 24 by 36 is standard; other sizes are available. Maximum size: 96 (W) by 60 (H) inches. For tempered glass, one dimension must be greater than 25 inches.</p>
782	<p>Adjustable tilt, stainless steel frame with integral stiffeners. Galvanized steel back secured to frame with concealed fasteners. Mirror: 1/4 inch float glass, triple silver plated with electro copper plated layer and thermosetting, infrared cured paint backing with Poly-Glaze finish. Conforms to ASTM C 1036. Includes wedge of extruded polystyrene between mirror and steel back.</p> <p>Options: Tempered glass; laminated glass; polished No. 8 stainless steel; bright annealed stainless steel; Plexiglass.</p>

G. Mirror Unit **MG**:

1. Basis of Design: **Bradley Corp., Model [____]**.
2. Size and Application: [18 by 30 inches (457 by 762 mm)] [__ by __ inches (____ by ____ mm)], [At each wash station] [Where indicated] [insert location description].

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Frame: [Stainless-steel angle, mitered and welded, with tamper- and theft-resistant installation.] [Stainless steel channel, mitered and welded, with tamper- and theft-resistant installation.] [Frameless.] [Adjustable tilt.]
4. Mirror:

- a. 1/4 inch (6 mm) thick, float glass, triple silvered, electro-copper plated with baked enamel finish.
- b. 1/4 inch (6 mm) thick, tempered glass, triple silvered, electro-copper plated with baked enamel finish.
- c. 1/4 inch (6 mm) thick, laminated glass, triple silvered, electro-copper plated with baked enamel finish.
- d. No. 8 polished stainless steel.
- e. Bright annealed stainless steel.
- f. Plexiglass mirror.

Facial Tissue Dispensers:

987	Recessed, galvanized cold-rolled steel cabinet with removable stainless steel faceplate with satin finish on exposed surfaces. Face is held to cabinet by friction catch. Capacity: One box of 100 facial tissues.
987-78	Same as Model 978, but with polished stainless steel faceplate.
987-11	Surface mounted, satin finish stainless steel. Hinged face with integral catch for service. Capacity: One box of 100 facial tissues.
987-36	Same as Model 987, but with capacity of on box of 300 facial tissues.

H. Facial Tissue Dispenser **FTD**:

- 1. Basis of Design: **Bradley Corp., Model [____]**.
- 2. Application: [Where indicated] [insert location description].

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

- 3. Exposed Finish and Base Material: [Satin stainless steel] [Polished stainless steel].
- 4. Capacity: One box of [100] [300] facial tissues.

2.4 PUBLIC-USE SHOWER ROOM ACCESSORIES

Shower Curtain Rods:

953	Straight shower curtain rod with stainless steel mounting flanges and exposed fasteners. 1 inch o.d. seamless stainless steel tubing with satin finish on exposed surfaces. Suitable for 36 to 72 inch shower stall. For 72 inch length and greater, also specify shower rod ceiling support. -78: Bright polished finish.
9531	Same as Model 953, but 1-1/4 inch o.d. tubing.
9530	Curved shower curtain rod with swiveled mounting brackets, satin finish. 1 inch o.d. seamless stainless steel tubing with satin finish on exposed surfaces. Supports 50 pounds. -60: 60 inch. -72: 72 inch. 0078: Bright polished finish.
9538	Same as Model 953, but with plastic mounting flanges and stainless steel snap-on escutcheons to conceal hardware.
9539	Same as Model 9538, but 1-1/4 inch o.d. tubing.

A. Shower Curtain Rod **SCR**:

- 1. Basis of Design: **Bradley Corp., Model [____]**.

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

2. Description: [1 inch (25 mm)] [1-1/4 inch (32 mm)] OD 0.05 inch (12.7 mm) thick stainless steel tubing, [curved] [straight].
3. Mounting Flanges: [Stainless-steel flanges with exposed fasteners.] [Plastic flanges with stainless steel snap-on escutcheons.] Provide ceiling bracket where recommended by manufacturer.
4. Finish: [Satin] [Bright polished].

Shower Curtains:

Width Tolerances: 36 inches: Plus or minus 3 inches. 42 inches: Plus or minus 1 inch. 48 inches: Plus or minus 1 inch. 54 inches: Plus or minus 5 inches. 72 inches: Plus or minus 3 inches.

- 9533 Antimicrobial 6 ga. vinyl shower curtain, white. Hemmed edges and aluminum grommets on 6 inch centers at top edge. Sizes: 36, 42, and 72 (W) by 72 (H) inches.
- 9534 8 oz. cotton duck shower curtain, white. Hemmed top edge and chrome plated nickel grommets on 6 inch centers. Various sizes.
- 9535 Antimicrobial 10 oz. nylon-reinforced vinyl shower curtain, green. Reinforced, flameproof, stain resistant, self-deodorizing fabric. Hemmed edges and aluminum grommets on 6 inch centers at top edge. Sizes: 42, 48, and 72 (W) by 72 (H) inches.
- 9537 Same as Model 9535: White.
- 9536 Shower curtain hook, stainless steel spring wire clip with snap fastener. Suitable for use with 1 inch and 1-1/4 inch shower curtain rods.
- 9540 Same as Model 9536, but includes 5 nickel plated brass rollers on each hook.

A. Shower Curtain **SC**:

1. Basis of Design: **Bradley Corp., Model [____]**.

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

2. Material: [Nylon-reinforced vinyl, minimum 10 oz./sq. yd. (237 g/sq. m)] [0.014 inch (0.36 mm)] thick vinyl, with integral antimicrobial agent] [Cotton duck, minimum 10 oz./sq. yd. (190 g/sq. m)]. Aluminum grommets on 6 inch (152 mm) centers.
 - a. Color: [White] [Green].
3. Shower Curtain Hooks: Stainless-steel, spring wire curtain hooks [with nickel plated brass rollers].

Folding Shower Seats:

- 9569 1 inch o.d. stainless steel tubing frame, stainless steel wall bracket, stainless steel retaining bracket, and melamine laminated seat over 1/2 inch solid phenolic core. Seat is field convertible to left or right hand "L" shaped configuration. Positive catch holds seat in up or down position. Static load limit: 250 lbs. Seat color: Matte white standard, or as selected from manufacturer's standard colors.
- 9562 Same as Model 9569 but rectangular configuration.
- 9591 Same as Model 9569 but square configuration.
- 957 1-1/4 inch o.d. stainless steel tubing frame with 1 inch o.d. cross members. free standing with stainless steel wall bracket, and melamine laminated seat over 1/2 inch solid phenolic core. Left hand "L" shaped seat. Positive catch holds seat in up or down position. Static load limit:

	900 lbs. Seat color: Matte white standard, or as selected from manufacturer's standard colors. 9571: Right hand seat.
958	1-1/4 inch o.d. stainless steel tubing frame with 1 inch o.d. cross members, free standing with stainless steel wall brackets, and melamine laminated seat over 1/2 inch solid phenolic core. Rectangular shaped seat. Positive catch holds seat in up or down position. Static load limit: 900 lbs. Seat color: Matte white standard, or as selected from manufacturer's standard colors.
9594	1 in o.d. stainless steel tubing frame, stainless steel wall bracket, stainless steel retaining bracket, and 1" thick, solid high-density polyethylene seat. Seat is field convertible to left or right hand "L" shaped configuration. Positive catch holds seat in up or down position. Static load limit: 250 lbs. Seat color: Linen with cobblestone textured finish.
9593	Same as Model 9594 but rectangular configuration
9592	Same as Model 9594 but square configuration.

B. Folding Shower Seat **FSS**:

1. Basis of Design: **Bradley Corp., Model [____]**.
2. Configuration: **[Rectangular] [Square] [Field convertible]** seat.
3. Color: Manufacturer's standard.
4. Seat: **[Laminated phenolic.] [High density polyethylene.]**
5. Frame and Mounting Mechanism: Stainless steel.
6. Static Load Capacity: **[250 lb. (113 kg)] [900 lb (408 kg)]**.

Soap Dishes:

900	Surface mounted, 7-gauge stainless steel, satin finish, formed as a single piece. Includes three drain holes.
901	Surface mounted, cast brass, nickel plated and highly polished chrome finish. -60 With 3 drain holes.
9014	Surface mounted, stainless steel with satin finish. Includes four drain holes. -63: Without drain holes.
9015	Same as Model 9014, but with bright polished stainless steel. -63 Without drain holes.
921	Surface mounted, die cast Zamac, copper nickel plated with highly polished chrome finish. Includes cadmium plated steel wall plate. -60 With drain holes.
9352	Recess mounted, bright polished stainless steel. Includes removable soap tray.
9353	Same as Model 9352, but satin stainless steel finish.
9362	Same as Model 9352, and includes matching towel bar.
9363	Same as Model 9353, and includes matching towel bar.
940	Recess mounted, satin finish stainless steel, integral towel bar. Includes mortar lugs.
9401	Same as model 940, but without towel bar.
9402	Same as Model 940, but with wall clamp in place of mortar lugs.
9403	Same as Model 9401, but with wall clamp in place of mortar lugs.

A. Soap Dish **SD**:

1. Basis of Design: **Bradley Corp., Model [____]**.

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

2. Mounting: **[Surface.] [Recessed.]**

3. [Recessed Mounting Fittings: [Mortar lugs.] [Wall clamp.]]
4. Material: [Stainless steel.] [Cast brass.] [Die cast Zamac.]
5. Finish: [Stainless steel, satin.] [Polished chrome.]
6. Drain Holes: [With.] [Without.]
7. [Matching] [Integral] Towel Bar: [Included.] [Not included.]

Robe Hooks:

- | | |
|------|---|
| 911 | Surface mounted clothes hook, chrome plated brass. Single hook. |
| 9111 | Surface mounted clothes hook, satin finish stainless steel. Single hook. |
| 9114 | Surface mounted, satin finish stainless steel. Single hook. |
| 9115 | Surface mounted, bright polished stainless steel. Single hook. |
| 9118 | Surface mounted robe hook, chrome plated brass. Single hook. |
| 9119 | Surface mounted clothes hook with concealed mounting hardware, chrome plated brass with chrome plated steel cover plate. Single hook. |
| 912 | Surface mounted clothes hook, chrome plated brass. Double hook. |
| 9124 | Surface mounted, satin finish stainless steel. Double hook. |
| 9125 | Surface mounted, bright polished stainless steel. Double hook. |
| 9134 | Surface mounted hat and coat hook, satin finish stainless steel. Single hook for each. |
| 9135 | Surface mounted hat and coat hook, bright polished stainless steel. Single hook for each. |
| 914 | Surface mounted clothes hook, chrome plated brass. Double hook. |
| 915 | Surface mounted clothes hook and door bumper, chrome plated brass. Single hook. |
| 931 | Surface mounted, die cast Zamac, copper nickel plated with highly polished chrome finish. Includes cadmium plated steel wall plate. Single hook. |
| 9311 | Surface mounted towel hook, die cast Zamac, copper nickel plated with highly polished chrome finish. Long projection (5-1/8 inches). Includes cadmium plated steel wall plate. Single hook. |
| 932 | Surface mounted, die cast Zamac, copper nickel plated with highly polished chrome finish. Includes cadmium plated steel wall plate. Double hook. |

A. Robe Hook RH:

1. Basis of Design: **Bradley Corp., [___]**.

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

2. Description: [Single] [Double] -prong unit, surface mounted.
3. Material and Finish: [Chrome plated Zamac, with zinc plated steel wall plate] [Bright polished stainless steel] [Satin stainless steel] [Chrome-plated brass] .

2.5 CHILDCARE ACCESSORIES

A. Diaper-Changing Stations DCS:

1. Basis of Design: **Bradley Corp., Model 961 Series.**

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

2. Description: ADA/ABA-compliant horizontal unit with fold-down platform from stored position, with safety strap.
3. Capacity: Not less than 100 lb (45.4 kg) per ASTM F 2285.
4. Mounting: Surface.
5. Operation: Concealed pneumatic gas shock.
6. Material and Finish: Molded high-density polyethylene, with full-length steel hinge pin.
7. Accessories: Integral liner dispenser and bag hook.
8. Color: As selected by Architect from manufacturer's standard colors.

B. Diaper-Changing Stations **DCS**:

1. Basis of Design: **Bradley Corp., Model 962 Series.**

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

2. Description: ADA/ABA-compliant horizontal unit with fold-down platform from stored position, with cam buckle safety strap.
3. Capacity: Not less than 250 lb (113.4 kg) per ASTM F 2285.
4. Mounting: [Surface] [Recessed].
5. Operation: Concealed pneumatic gas shock.
6. Material and Finish: Stainless steel exterior, brushed finish, with molded high-density polyethylene body and full-length steel hinge pin.
7. Accessories: Integral liner dispenser and bag hook.
8. Color: As selected by Architect from manufacturer's standard colors.

2.6 CUSTODIAL ACCESSORIES

A. Corner Guard **CG**:

1. Basis of Design: **Bradley Corp., Model 991.**
2. Description: Self adhesive angle.
3. Materials: Stainless steel.
4. Mounting: Surface mounted, peel and stick adhesive tape.
5. Dimensions: 3-1/2 by 3-1/2 by 40 inches (89 by 89 by 1016 mm).

Bradley Decorative Wall Trim: Bradley Wave accent wall trim coordinates with Frequency fixtures.

B. Utility Shelf **US**:

1. Basis of Design: **Bradley Corp., Model [____].**
2. Application: [One unit per janitor closet] [Where indicated] [insert location description].

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Description: Metal plate with attached hooks, mop-broom handle holding mechanisms, and 8 inch (203 mm) deep shelf across full width of unit.
4. Materials: Stainless steel. Mop-broom handle holders include rubber cams.
5. Mounting: Surface mounted.
6. Quantity of Hooks/Mop-Broom Holders: [4/3] [5/4].
7. Size: [14 by 34 inch (356 by 864 mm)] [14 by 44 inch (356 by 1118 mm)].

Bradley Mop and Broom Holders:

9953 Stainless steel wall-mounted unit with rubber cam mop/broom holders for custodial operations. 3 mop holders, 24 inches long. 9954: 4 mop holders, 36 inches long. 9955: 5 mop holders, 48 inches.

C. Mop and Broom Holder **MOP**:

1. Basis of Design: **Bradley Corp., Model [____]**.
2. Application: **[One unit per janitor closet] [Where indicated] [insert location description]**.

Specifier: If required, retain descriptive characteristics below and edit to match specified model.

3. Description: Metal plate with attached mop-broom handle holding mechanisms.
4. Materials: Stainless steel. Mop-broom handle holders include rubber cams.
5. Finish: Satin stainless steel.
6. Mounting: Surface mounted.
7. Length: **[24 inches (610 mm).] [36 inches (915 mm).] [48 inches (1220 mm).]**
8. Quantity of Hooks/Mop-Broom Holders: **[3] [4] [5]**.

2.7 FABRICATION

- A. General: Fabricate units with tight seams and joints, and exposed edges rolled. Hang doors and access panels with full-length, continuous hinges. Equip units for concealed anchorage and with corrosion-resistant backing plates.
- B. Keys: Provide universal keys for internal access to accessories for servicing and resupplying. Provide minimum of six keys to Owner's representative.

PART 3 - EXECUTION

3.1 INSTALLATION

- A. Assemble fixtures and associated fittings and trim in accordance with manufacturer's instructions.
- B. Install supports attached to building structure for equipment requiring supports.
- C. Grab Bars: Install grab bars to withstand downward force of not less than 250 lbf (1112 N) per ASTM F 446.
- D. Install equipment level, plumb, and firmly in place in accordance with manufacturer's rough-in drawings.

3.2 CLEANING AND PROTECTION

- A. Repair or replace defective work, including damaged equipment and components.
- B. Clean unit surfaces, and leave in ready-to-use condition.

C. Turn over keys, tools, maintenance instructions, and maintenance stock to Owner.

3.3 TESTING AND ADJUSTING

A. Test each piece of equipment provided with moving parts to assure proper operation, freedom of movement, and alignment. Install new batteries in battery-powered items.

B. Repair or replace malfunctioning equipment, or equipment with parts that bind or are misaligned.

END OF SECTION