



INSTANTANEOUS WATER HEATER SYSTEM WITH A BUFFER TANK AND RECIRCULATION LOOP. EXPANSION TANK IS TYPICALLY INSTALLED ON THE COLD WATER INLET BUT CAN BE INSTALLED ON THE HOT WATER SUPPLY AFTER THE WATER HEATER. THE USE OF THE BUFFER TANK IS TO ASSIST IN A LARGE INSTANTANEOUS DEMAND.

THIS DIAGRAM IS ONLY A SUGGESTED PLUMBING SCHEMATIC AND MAY NOT INCLUDE ALL STATE/LOCAL CODE REQUIRED EQUIPMENT, VALVE, ETC.

THE PUMP CAN BE CONTROLLED BY TEMPERATURE (AQUASTAT), TIMER, OR OCCUPANCY SENSOR TO MAINTAIN LOOP AT USAGE TEMPERATURE.

ALL EQUIPMENT AND PIPING SHALL BE SIZED BY CONSULTANT/ENGINEER.

ANY QUESTIONS REGARDING THE KELTECH HEATER, HOW IT CAN BE UTILIZED, OR CHANGES TO THE SYSTEM SHOULD BE SENT TO BRADLEY CORP. ATTN: NICK GREENE

- INDUSTRIAL APPLICATIONS
- MEAT PACKING PLANTS
 - DAIRIES
 - CAR WASHES
 - TRUCK WASHING
 - AIRPLANES – CLEANING/DE-ICING
 - PRE-HEAT FOR PRESSURE WASHERS

DATE	REV	DESCRIPTION	ECN	BY
REVISION HISTORY				
Bradley		This print contains information that is PROPRIETARY. Disclosure of any information on this document cannot be made without written permission of Bradley Corporation.		
TOLERANCES UNLESS OTHERWISE SPECIFIED		DRAWN BY:	NJG	
		DATE:	10/22/14	
		SCALE:	NTS	
		FIRST USED:		
		REF:		
MATERIAL: XXXXXXXXXXXX				
NAME: XXXXXX XXXXXX				
DWG NUMBER: XXX-XXX				SHEET 1 OF 1