

Cleaning Plastic

- Routine cleaning should be performed with a soft, wet cloth.
- Stubborn dirt and grease can be removed with a mild cleaning solution (we recommend "Simple Green" or "DoAll") and a cloth or SOFT bristled brush.
- Graffiti can usually be removed with industrial "Graffiti Remover". Make sure to test in an inconspicuous area, as some of these products can damage the plastic surface or cause a haze.
- DO NOT use abrasive pads (ScotchBrite type or steel wool) or abrasive cleansers. They will leave scratch marks in the plastic.

Cleaning Stainless Steel Components

- DO NOT use abrasive cleaners or cleaners containing bleach.
- Use only soft cloth, sponge, fibrous brushes, plastic or stainless steel pads.
- Rinse thoroughly with fresh water after every cleaning operation.
- Always wipe dry to avoid water marks.
- WD-40 may be used to protect hinges and fasteners from exposure to water, chlorine and salt air.

Repairing Scratches

- Small scratches can be smoothed out by pushing the raised material down with the back of a spoon or a blunt screwdriver.
- Small scratches ("marred" areas) can be reduced by lightly passing the flame from an acetylene torch over the area. This must be done quickly and at a distance of about 6 inches to avoid melting the plastic.

Replacing Old Style Number Plates

- Numbers plates can be pried out with a thin file or knife and reused.
- New number plates (HW0011) can also be purchased directly thru the following company:

E.R. Perry Signs & Engraving LLC
218-387-9479
signs@erperry.com

Replacing New Style (metal hinge) Locker Doors

1. Remove the screws that secure the door to the hinge (there are screws on the face and edge of the door). The screws are T-20 security-type torx head.
2. Remove the damaged door. Attach the face of the door to the hinge with screws in predrilled holes. Do not tighten screws all the way at this point.
3. Drill 3/8"-1/2" deep pilot holes for screws in edge of the door with 7/64" drill bit. Use holes in hinge as a guide and make sure to keep the drill parallel to the face of the door. Insert screws and tighten completely.
4. Go back and completely tighten screws on face of door.