

INTRODUCING

Gravity-Fed Safety Showers



Bradley's NEW Gravity Fed Safety Showers are designed for areas without a plumbed water supply.

Durable, heavy duty steel frame and water tank detach for easier transporting, installation and maintenance.

Industrial Solutions. Brought to Life.



NEW

S19390 Series Gravity Fed Safety Showers

Designed and engineered for locations without a plumbed water supply, Bradley's Gravity Fed Safety Showers are ideal for cold climate or indoor applications.

- **General area and hazardous location** models
- **550 gallon tank** delivers ANSI/ISEA Z358.1 required 15 minute flush for simultaneous drench shower and eye/face wash activation
- **Heavy duty steel frame, tank and enclosure detach** for easier transporting, installation and maintenance
- **Integral forklift slots** on tanks and enclosures
- Frame and tank enclosure designed to meet **International Building Code and ASCE Code**
- Easy to see **water level and temperature indicators**
- **High-visibility** BradTect® yellow coating
- **Halo eye/facewash** for 85% facial coverage and 20% better protection – the best contaminant relief available through superior coverage and wash pattern
- Optional **Signaling System**



Model S19390

Steel frame constructed with 2" square steel beams and welded joints. When secured properly, the frame structure is designed to meet wind loads of 82 mph.



Model S19392

100% Fiberglass surround construction; Flame-retardant resin with a Class 1 Flame Spread Index per ASTM E-84; Multi-directional drainage system; Insulation factor protection rating R-8 (ASTM C518).



UL Classified to ANSI/ISEA Z358.1



UL Listed Industrial Control Panel(s) for US and Canada
Designed to the National Electrical Code (NEC/NFPA70)

Visit bradleycorp.com for technical information

bradleycorp.com
800 BRADLEY +1 262 251 6000
W142 N9101 Fountain Boulevard
Menomonee Falls, WI USA 53051
4281-2.5-1218

