

#### Model 5402 — BradEX®



#### **Product Materials**

**CABINET:** 22 gauge stainless steel with exposed surfaces in architectural satin finish. Welded construction with burr-free edges.

**SERVICE DOOR:** 22 gauge stainless steel with exposed surfaces in architectural satin finish and tumbler lock keyed like other Bradley units. Hinged at bottom.

**SPINDLES:** Molded polyethylene.

# **Capacity**

Two standard core toilet tissue rolls through 5" in diameter.

## **Operation**

Cabinet holds two rolls of 4½" x 5" standard core toilet tissue, one above the other. When first roll is used up, fresh roll automatically drops down for use. Unique retaining mechanism prevents use of spare roll until first roll is completely used. Spindles non-removable by user. Hinged door permits access to storage compartment for servicing of unit.

#### Installation

Verify all rough-in dimensions prior to installation. Secure to wall with mounting screws (not included) at holes provided. Mounting Kit #899-027 available from Bradley. Visit www.bradleycorp.com for more information. Provide in-wall backing at mounting screw locations.

### **Guide Specification**

Surface-mounted dual roll toilet tissue dispenser shall be heavy gauge satin finish stainless steel and hold two standard core toilet tissue rolls.

Overall dimensions: 5\%"W x 10\%"H x 5\%"D.


# **& ADA Compliant**

Consult local and national accessibility codes for proper installation guidelines.

Conformity and compliance to local and national codes is the responsibility of the installer.

Orders composed of products indicated as **BradEX®** will be available to ship in three days after receipt of order at the factory. There is no pricing penalty for this service from Bradley.

Page 1 of 1 1/31/2024
This information is subject to change without notice.
Bradley\_TPDispenser\_5402



Dim. "A" Key Surface:	For Dim. "A"	Top of Unit	Bottom of Unit
Bottom of toilet paper opening to finished floor	20" (508mm)	30¼" (768mm)	197⁄8" (505mm)
	19" (483mm)	29¼" (743mm)	181⁄8" (479mm)
	18" (457mm)	28¼" (718mm)	171⁄8" (454mm)
	17" (432mm)	27¼" (692mm)	161/8" (429mm)
	16" (406mm)	26¼" (667mm)	151/8" (403mm)
	15" (381mm)	25¼" (641mm)	141/⁄8" (378mm)
Rough wall opening:			
Surface Mount:	No rough opening, see overall dimensions		

View Latest Version

© 2024 Bradley
P.O. Box 309, Menomonee Falls, WI 53052-0309
800 BRADLEY (800 272 3539) +1 262 251 6000
bradleycorp.com