



# DISCONTINUED

## 7481 Stainless Steel Mirror

**Unbreakable, bright annealed stainless steel mirror:**  
**Model 7481-XXXX (Specify width and height)**

### Product Materials

**MIRROR:** 20 gauge bright annealed stainless steel. Material is stretcher-leveled for uniformity. Surface is bright and smooth with mirror-like finish. A ¼" return conceals backing.

**BACKING:** Tempered Masonite bonded to mirror with adhesive.

☒ Stainless steel mirrors will differ in optic quality from glass mirrors.

### Installation

Verify all rough-in dimensions prior to installation. Secure to wall with tamper-resistant mounting screws (included) at holes provided. Provide in-wall backing at mounting screw locations.

### Guide Specification

Mirror shall be fabricated of bright annealed stainless steel with smooth reflective finish. Unit shall have ¼" return to conceal ¼" tempered Masonite backing bonded to mirror with adhesive. If either the width or height exceed 24", an additional hole will be added on each side.

**Stainless Steel Mirror shall be Bradley Model 7481-\_\_\_\_\_ " W x \_\_\_\_\_ " H (specify width and height).**

Model 7481 series stainless steel mirrors can be fabricated to a maximum size of 47"W x 72"H.

☒ In larger sizes, these units are subject to distortion and/or "oil canning" for which Bradley Corporation cannot accept responsibility.

### ADA Compliant

- ☒ Consult local and national accessibility codes for proper installation guidelines.
- ☒ Conformity and compliance to local and national codes is the responsibility of the installer.

Dim. "A" Key Surface:	For Dim. "A"	Bottom of Unit
Mirror's bottom edge of the reflecting surface to finished floor	40" (1016mm)	40" (1016mm)
	37" (940mm)	37" (940mm)
	34" (864mm)	34" (864mm)
<b>Rough wall opening:</b>		
Surface Mount:	No rough wall opening, see overall dimensions	

