

- Fixed mounting system
- Accommodates 60" or 72" shower stall
- Increases space in shower stall

Model 9530-600000 (60") **Bradex**® Model 9530-720000 (72")

NOTE: Curtain rods only available in 60" or 72" lengths.

Product Materials

FIXED BRACKETS: Stainless steel construction with exposed surfaces. Inside angle is 67.5 degrees.

TUBING: 1" diameter stainless steel, seamless construction with exposed surfaces in architectural satin finish.

Installation

Verify all rough-in dimensions prior to installation. Screws and anchors provided with swivel brackets. For additional installation instructions, visit bradleycorp.com.


When retrofitting or replacing a straight shower rod with Model 9530 curved shower rod, mount the new flange at the same location as the old flange. This will maximize the additional space a curved shower rod is designed to provide.


If properly mounted, the shower rod will withstand a maximum load of 50 lb without any sign of a permanent deflection.


Guide Specification

Shower curtain rod shall be fabricated of 20 gauge stainless steel in satin finish.









Orders composed of products indicated as **Bradex®** will be available to ship in three days after receipt of order at the factory. There is no pricing penalty for this service from Bradley.

Page 1 of 1 3/3/2025
This information is subject to change without notice.
Bradley_ShowerCurtainRod_9530

View Latest Version

© 2025 Bradley
P.O. Box 309, Menomonee Falls, WI 53052-0309
800 BRADLEY (800 272 3539) +1 262 251 6000
bradleycorp.com